




(86) Date de dépôt PCT/PCT Filing Date: 1998/08/18
(87) Date publication PCT/PCT Publication Date: 1999/02/25
(45) Date de délivrance/Issue Date: 2008/05/20
(85) Entrée phase nationale/National Entry: 2000/02/14
(86) N° demande PCT/PCT Application No.: US 1998/017115
(87) N° publication PCT/PCT Publication No.: 1999/009490
(30) Priorité/Priority: 1997/08/18 (US60/056342)

(51) Cl.Int./Int.Cl. *H04L 12/54* (2006.01),
H04L 12/16 (2006.01), *H04L 9/32* (2006.01)
(72) Inventeurs/Inventors:
COLLISON, DEREK L., US;
LESHCHINER, DAN, US;
PAGE, DENNIS R., US
(73) Propriétaire/Owner:
TIBCO SOFTWARE, INC., US
(74) Agent: SIM & MCBURNEY

(54) Titre : LIVRAISON ET MISE EN ATTENTE CERTIFIEES DE MESSAGES DANS DES COMMUNICATIONS A
DIFFUSION/ABONNEMENT MULTIPOINT
(54) Title: CERTIFIED MESSAGE DELIVERY AND QUEUING IN MULTIPOINT PUBLISH/SUBSCRIBE
COMMUNICATIONS



(57) Abrégé/Abstract:

A method for certified delivery of an outgoing message or messages in a multipoint anonymous, publish/subscribe telecommunications system. The system for utilizing the method and program product is one having at least one publisher (10) and

(57) **Abrégé(suite)/Abstract(continued):**

at least one subscriber (20). The method is carried out by first establishing a certified delivery session ledger. Next each outgoing message is labeled with a label including the delivery session name and a sequence number. The labeled outgoing message or messages are then sent to subscribers, and received by a subscriber. Various protocols are described.

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁶ : G06F 15/16</p>	<p>(11) International Publication Number: WO 99/09490</p> <p>(43) International Publication Date: 25 February 1999 (25.02.99)</p>
<p>(21) International Application Number: PCT/US98/17115</p> <p>(22) International Filing Date: 18 August 1998 (18.08.98)</p> <p>(30) Priority Data: 60/056,342 18 August 1997 (18.08.97) US</p> <p>(71) Applicant (for all designated States except US): REUTERS LTD. [GB/GB]; 85 Fleet Street, London EC4P 4AJ (GB).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): COLLISON, Derek, L. [US/US]; 232 Ross Lane, Foster City, CA 94404 (US). LESHCHINER, Dan [US/US]; Apartment 229, 141 Del Medio Avenue, Mountain View, CA 94040 (US). PAGE, Dennis, R. [US/US]; 201 Ada Avenue #35, Mountain View, CA 94043-4943 (US).</p> <p>(74) Agents: GOLDMAN, Richard, M.; Cooley Godward LLP, 3000 El Camino Real, Five Palo Alto Square, Palo Alto, CA 94306-2155 (US) et al.</p>	<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>

(54) Title: **CERTIFIED MESSAGE DELIVERY AND QUEUING IN MULTIPOINT PUBLISH/SUBSCRIBE COMMUNICATIONS**

(57) Abstract

A method for certified delivery of an outgoing message or messages in a multipoint anonymous, publish/subscribe telecommunications system. The system for utilizing the method and program product is one having at least one publisher (10) and at least one subscriber (20). The method is carried out by first establishing a certified delivery session ledger. Next each outgoing message is labeled with a label including the delivery session name and a sequence number. The labeled outgoing message or messages are then sent to subscribers, and received by a subscriber. Various protocols are described.

What is claimed is:

1. In a computer-based publish/subscribe system having a subscriber application that has previously subscribed to receive a particular type of message, a computer-implemented method for establishing a certified messaging session between a publisher application and the subscriber application, the computer-implemented method comprising:

receiving, at the publisher application, a certified messaging subscription request, said certified messaging subscription request including a subscriber name identifying the subscriber application and a subject name associated with and identifying the particular type of message for which the certified messaging session is to be established;

responsive to receiving the certified messaging subscription request, establishing the certified messaging session with the subscriber application by adding the subscriber name to a message ledger at the publisher application, and communicating an acknowledgment message to the subscriber application, the acknowledgment message to acknowledge the establishment of the certified messaging session;

attempting to deliver a certified message of the particular type in accordance with the certified messaging session by assigning a sequence number to the certified message, communicating the certified message from the publisher application to the subscriber application, recording a delivery attempt of the certified message in the ledger, and retaining the certified message in the ledger at least until the publisher application has received a confirmation message from the subscriber application, the confirmation message confirming receipt of the certified message at the subscriber application; and

communicating a confirmation request from the publisher application to the subscriber application if the publisher application has not received a confirmation message from the subscriber application within a predetermined period of time after attempting to

deliver the certified message identified by the assigned sequence number, the confirmation request requesting that the subscriber application acknowledge receipt of the certified message identified by the assigned sequence number.

2. The computer-implemented method of claim 1, further comprising:

responsive to receiving, at the publisher application, a confirmation message confirming receipt of the certified message identified by the assigned sequence number at the subscriber application, updating the ledger at the publisher application to indicate the certified message identified by the assigned sequence number was received by the subscriber application.

3. The computer-implemented method of claim 1, further comprising:

responsive to receiving, at the publisher application, a confirmation message confirming receipt of the certified message identified by the assigned sequence number at the subscriber application, deleting the certified message identified by the assigned sequence number from the ledger at the publisher application.

4. The computer-implemented method of claim 1, further comprising:

responsive to receiving, at the publisher application, a confirmation message confirming receipt of the certified message identified by the assigned sequence number at the subscriber application, deleting the certified message identified by the assigned sequence number from the ledger if the ledger indicates that all subscriber applications, to which the certified message identified by the assigned sequence number has been sent, have confirmed receipt of the certified message identified by the assigned sequence number.

5. The computer-implemented method of claim 1, wherein the ledger is a file-based ledger, and the certified messaging session is persistent beyond termination and restart of the publisher application and/or the subscriber application.

6. The computer-implemented method of claim 1, wherein prior to establishing the certified messaging session with the subscriber application, the publisher application, with which the subscriber application has previously subscribed for a particular type of message, publishes messages that are communicated to the subscriber application without the publisher application having knowledge of the existence of the subscriber application.

7. In a computer-based publish/subscribe system having a subscriber application that has previously subscribed for a particular type of message, a computer-implemented method for establishing a certified messaging session between a publisher application and the subscriber application, the computer-implemented method comprising:

communicating a certified messaging subscription request from the subscriber application to the publisher application, said certified messaging subscription request including a subscriber name identifying the subscriber application and a subject name associated with and identifying the particular type of message for which the certified messaging session is to be established;

receiving, at the subscriber application, an acknowledgement message from the publisher application, said acknowledgment message acknowledging the establishment of the certified messaging session;

receiving, at the subscriber application, a certified message from the publisher application in accordance with the certified messaging session, the certified message identified by a sequence number;

responsive to receiving, at the subscriber application, the certified message identified by the sequence number from the publisher application, updating a ledger at the subscriber application to indicate the receipt of the certified message identified by the sequence number, and communicating a confirmation message to the publisher application, the confirmation

message confirming receipt of the certified message identified by the sequence number at the subscriber application; and

after communicating a confirmation message to the publisher application, receiving a confirmation request from the publisher application, the confirmation request requesting a confirmation message from the subscriber application to confirm receipt of a certified message having a particular sequence number.

8. The computer-implemented method of claim 7, further comprising:

verifying whether the ledger indicates a certified message having the particular sequence number has been received at the subscriber application, and if so, communicating a second confirmation message to the publisher application, the second confirmation message confirming receipt of the certified message having the particular sequence number at the subscriber application.

9. The computer-implemented method of claim 7, further comprising:

after receiving a confirmation request from the publisher application, receiving a second certified message having a sequence number indicating a previous certified message was sent by the publisher application, but not received by the subscriber application; and

communicating a certified message request to the publisher application, the certified message request including a sequence number associated with a certified message that the ledger indicates was not previously received at the subscriber application.

10. The computer-implemented method of claim 7, wherein the ledger is a file-based ledger, and the certified messaging session is persistent beyond termination and restart of the publisher application and/or the subscriber application.

11. A publisher application for communicating certified messages to a subscriber application via a certified messaging session, the publisher application and the subscriber

application part of an anonymous publish/subscribe computer system, the publisher application comprising:

a process to receive a certified messaging subscription request, said certified messaging subscription request including a subscriber name identifying the subscriber application and a subject name associated with and identifying the particular type of message for which the certified messaging session is to be established;

a process to establish the certified messaging session with the subscriber application in response to receiving the certified messaging subscription request by adding the subscriber name to a message ledger at the publisher application, and communicating an acknowledgment message to the subscriber application, the acknowledgment message to acknowledge the establishment of the certified messaging session; and

a certified delivery process to attempt to deliver a certified message of the particular type in accordance with the certified messaging session by assigning a sequence number to the certified message, communicating the certified message from the publisher application to the subscriber application, recording a delivery attempt of the certified message in the ledger, and retaining the certified message in the ledger at least until the publisher application has received a confirmation message from the subscriber application, the confirmation message confirming receipt of the certified message at the subscriber application, wherein the certified delivery process is to communicate a confirmation request to the subscriber application if the publisher application has not received a confirmation message from the subscriber application within a predetermined period of time after attempting to deliver the certified message identified by the assigned sequence number, the confirmation request requesting that the subscriber application acknowledge receipt of the certified message identified by the assigned sequence number.

12. The publisher application of claim 11, wherein, responsive to receiving, at the publisher application, a confirmation message confirming receipt of the certified message identified by the assigned sequence number at the subscriber application, the certified delivery process is to delete the certified message identified by the assigned sequence number from the ledger at the publisher application.

13. The publisher application of claim 11, wherein, responsive to receiving, at the publisher application, a confirmation message confirming receipt of the certified message identified by the assigned sequence number at the subscriber application, the certified delivery process is to delete the certified message identified by the assigned sequence number from the ledger if the ledger indicates that all subscriber applications, to which the certified message identified by the assigned sequence number has been sent, have confirmed receipt of the certified message identified by the assigned sequence number.

14. The publisher application of claim 11, wherein the ledger is a file-based ledger, and the certified messaging session is persistent beyond the publisher application or the subscriber application being terminated and restarted.

15. The publisher application of claim 11, further comprising:

a messaging process to publish messages with a subject name associated with content of the messages, the messages communicated to subscriber applications that have subscribed to receive messages having a particular subject name without the publisher application having knowledge of the existence of the subscriber application.

16. The publisher application of claim 11, wherein, responsive to receiving, at the publisher application, a confirmation message confirming receipt of the certified message identified by the assigned sequence number at the subscriber application, updating the ledger

at the publisher application to indicate the certified message identified by the assigned sequence number was received by the subscriber application.

17. A subscriber application for receiving certified messages from a publisher application via a certified messaging session, the publisher application and the subscriber application part of an anonymous publish/ subscribe computer system, the subscriber application comprising:

a process to communicate a certified messaging subscription request from the subscriber application to the publisher application, said certified messaging subscription request including a subscriber name identifying the subscriber application and a subject name associated with and identifying the particular type of message for which the certified messaging session is to be established;

a process to receive, at the subscriber application, an acknowledgement message from the publisher application, said acknowledgment message acknowledging the establishment of the certified messaging session; and

a certified delivery process to receive, at the subscriber application, a certified message from the publisher application in accordance with the certified messaging session, the certified message identified by a sequence number, and responsive to receiving the certified message identified by the sequence number from the publisher application, to update a ledger at the subscriber application to indicate the receipt of the certified message identified by the sequence number, and to communicate a confirmation message to the publisher application, the confirmation message confirming receipt of the certified message identified by the sequence number at the subscriber application, wherein, after communicating a confirmation message to the publisher application, the certified message process is to receive a confirmation request from the publisher application, the confirmation request requesting a confirmation message from the subscriber application to confirm receipt of a certified message having a particular sequence number.

18. The subscriber application of claim 17, wherein the certified message process is to verify whether the ledger indicates a certified message having the particular sequence number has been received at the subscriber application, and if so, to communicate a second confirmation message to the publisher application, the second confirmation message confirming receipt of the certified message having the particular sequence number at the subscriber application.

19. The subscriber application of claim 17, wherein, after receiving a confirmation request from the publisher application, the certified message process is to receive a second certified message having a sequence number indicating a previous certified message was sent by the publisher application, but not received by the subscriber application, and wherein the certified message process is to communicate a certified message request to the publisher application, the certified message request including a sequence number associated with a certified message that the ledger indicates was not previously received at the subscriber application.

20. The subscriber application of claim 17, wherein the ledger is a file-based ledger, and the certified messaging session is persistent beyond the publisher application or the subscriber application being terminated and restarted.

**CERTIFIED MESSAGE DELIVERY AND QUEUING IN MULTIPOINT
PUBLISH/SUBSCRIBE COMMUNICATIONS**

BACKGROUND TO THE INVENTION

5

Technical Field

This invention relates to multipoint publish/subscribe communications and, more particularly, to certified message delivery and queuing between multipoint computer-based publisher and subscriber applications.

10

Background

In a typical anonymous public/subscribe technologies -- such as described in US patents 5,557,798; 5,339,392; 5,257,369 and 5,187,787 -- a publisher application publishes information to requesting or subscriber applications without having any
15 knowledge of the number, identity or address of any such subscriber applications. In fact, no subscriber applications may exist. Instead of knowing about subscribers, a publisher will merely publish information applying a context or subject "label" to the published message. A subscriber then identifies desired messages by the content label and receives only those messages relevant to the desired content.

20

The advantages of such a publish/subscribe, content-based addressing systems are well known and include the ability to decouple subscribers and publishers from one another. This decoupling allows publishers and subscribers to operate without having any knowledge of the identity, location or address, or communication protocols of each
25 other. The flexibility that this offers is enormous and, accordingly, such content/subject-based addressing communication-environments are becoming increasingly popular.

30

Unfortunately, the very advantages (such as anonymous decoupling) of these systems, precludes the use of conventional reliable messaging protocols such as TCP. TCP, and other reliable messaging protocols apply only in point-to-point type of communications. In these point-to-point communications message senders and

receivers are directly linked to one another and therefore know each other's addresses and locations.

5 Unfortunately, these reliable messaging protocols -- that guarantee arrival and order of arrival of messages -- require advance knowledge between applications. They are, therefore, not applicable to typical publish/subscribe environments.

10 Yet, such reliable or certified delivery of messages is extremely important. For example, certified delivery is appropriate when a sending application requires individual confirmation of delivery for each message it sends. For example, a travelling sales representative computes sales figures on a lap-top computer, and sends them to a supervisor at the office. The user must know for certain that the data has arrived, and has been included in the supervisor's sales report.

15 Certified delivery is also appropriate when a receiving application cannot afford to miss any messages. For example, in an application that processes orders to buy and sell inventory items, each order is important. If any orders are omitted, then inventory records are incorrect.

20 In addition, certified delivery is appropriate when each message on a specific subject builds upon information in the previous message with that subject. For example, a sending program updates a receiving database, contributing part of the data in a record, but leaving other parts of the data unchanged. The database is correct only if all updates arrive in the order they are sent.

25 Furthermore, certified delivery is appropriate in situations of intermittent physical connectivity--such as discontinuous network connections, for example, an application in which several mobile lap-top computers must communicate with one another. Connectivity between mobile units is sporadic, requiring persistent storage of messages
30 until the appropriate connections are reestablished.

Thus, a very real need exists for having both the advantages of certified messaging and the advantages of content-based, anonymous publish/subscribe environments.

SUMMARY OF THE INVENTION

Briefly, according to this invention a publisher publishes a message to any number of unknown subscribers. Note, as used herein "publisher" and "sender" are used synonymously, and "subscriber" and "listener" are used synonymously. The message
5 is published indicating the subject or content using typical content-based publish/subscribe protocols. Subscribers interested in receiving information on the designated content receive the message without knowing about the publisher. Thus the publisher information remains transparent to the subscriber:

10 In circumstances where the certified messaging is required, the invention provides for establishing a message delivery tracking session. This session includes a name and a ledger used for tracking.

Using these functions the system can track delivery of messages and notify
15 publishers/senders if messages are not delivered. In one embodiment of the invention, delivery attempts are repeated for a preset time (or number of delivery attempts) to ensure or attempt to ensure delivery.

This invention also extends to queuing messages for certified delivery. This occurs
20 when certified delivery is required for a one of a group of n possible recipients. The system ensures that one (and not all) of the group receives the message. This is accomplished by having members of the group indicate their availability or capacity and having the system route the message to the subscriber (listener) with the greatest availability.

25 An extension of this concept is the scheduling of tasks for a group of n possible task performers, each available to accomplish a task. Each task doer, notifies the system of its availability/ability to accomplish tasks. Tasks are then sent to/queued for each task doer according to a rating based on its availability.

Accordingly, in one aspect of the present invention there is provided in a computer-based publish/subscribe system having a subscriber application that has previously subscribed to receive a particular type of message, a computer-implemented method for establishing a certified messaging session between a publisher application and the subscriber application, the computer-implemented method comprising:

receiving, at the publisher application, a certified messaging subscription request, said certified messaging subscription request including a subscriber name identifying the subscriber application and a subject name associated with and identifying the particular type of message for which the certified messaging session is to be established;

responsive to receiving the certified messaging subscription request, establishing the certified messaging session with the subscriber application by adding the subscriber name to a message ledger at the publisher application, and communicating an acknowledgment message to the subscriber application, the acknowledgment message to acknowledge the establishment of the certified messaging session;

attempting to deliver a certified message of the particular type in accordance with the certified messaging session by assigning a sequence number to the certified message, communicating the certified message from the publisher application to the subscriber application, recording a delivery attempt of the certified message in the ledger, and retaining the certified message in the ledger at least until the publisher application has received a confirmation message from the subscriber application, the confirmation message confirming receipt of the certified message at the subscriber application; and

communicating a confirmation request from the publisher application to the subscriber application if the publisher application has not received a confirmation message from the subscriber application within a predetermined period of time after attempting to deliver the certified message identified by the assigned sequence number, the confirmation request requesting that the subscriber application acknowledge receipt of the certified message identified by the assigned sequence number.

According to another aspect of the present invention there is provided in a computer-based publish/subscribe system having a subscriber application that has previously subscribed for a particular type of message, a computer-implemented method for establishing a certified messaging session between a publisher application and the subscriber application, the computer-implemented method comprising:

communicating a certified messaging subscription request from the subscriber application to the publisher application, said certified messaging subscription request including a subscriber name identifying the subscriber application and a subject name associated with and identifying the particular type of message for which the certified messaging session is to be established;

receiving, at the subscriber application, an acknowledgement message from the publisher application, said acknowledgment message acknowledging the establishment of the certified messaging session;

receiving, at the subscriber application, a certified message from the publisher application in accordance with the certified messaging session, the certified message identified by a sequence number;

responsive to receiving, at the subscriber application, the certified message identified by the sequence number from the publisher application, updating a ledger at the subscriber application to indicate the receipt of the certified message identified by the sequence number, and communicating a confirmation message to the publisher application, the confirmation message confirming receipt of the certified message identified by the sequence number at the subscriber application; and

after communicating a confirmation message to the publisher application, receiving a confirmation request from the publisher application, the confirmation request requesting a confirmation message from the subscriber application to confirm receipt of a certified message having a particular sequence number.

According to yet another aspect of the present invention there is provided a publisher application for communicating certified messages to a subscriber application via a certified messaging session, the publisher application and the subscriber application part of an anonymous publish/subscribe computer system, the publisher application comprising:

a process to receive a certified messaging subscription request, said certified messaging subscription request including a subscriber name identifying the subscriber application and a subject name associated with and identifying the particular type of message for which the certified messaging session is to be established;

5 a process to establish the certified messaging session with the subscriber application in response to receiving the certified messaging subscription request by adding the subscriber name to a message ledger at the publisher application, and communicating an acknowledgment message to the subscriber application, the acknowledgment message to acknowledge the establishment of the certified
10 messaging session; and

a certified delivery process to attempt to deliver a certified message of the particular type in accordance with the certified messaging session by assigning a sequence number to the certified message, communicating the certified message from the publisher application to the subscriber application, recording a delivery attempt of
15 the certified message in the ledger, and retaining the certified message in the ledger at least until the publisher application has received a confirmation message from the subscriber application, the confirmation message confirming receipt of the certified message at the subscriber application, wherein the certified delivery process is to communicate a confirmation request to the subscriber application if the publisher
20 application has not received a confirmation message from the subscriber application within a predetermined period of time after attempting to deliver the certified message identified by the assigned sequence number, the confirmation request requesting that the subscriber application acknowledge receipt of the certified message identified by the assigned sequence number.

25 According to still yet another aspect of the present invention there is provided a subscriber application for receiving certified messages from a publisher application via a certified messaging session, the publisher application and the subscriber application part of an anonymous publish/ subscribe computer system, the subscriber application comprising:

30 a process to communicate a certified messaging subscription request from the subscriber application to the publisher application, said certified messaging subscription request including a subscriber name identifying the subscriber

application and a subject name associated with and identifying the particular type of message for which the certified messaging session is to be established;

a process to receive, at the subscriber application, an acknowledgement message from the publisher application, said acknowledgment message
 5 acknowledging the establishment of the certified messaging session; and

a certified delivery process to receive, at the subscriber application, a certified message from the publisher application in accordance with the certified messaging session, the certified message identified by a sequence number, and responsive to receiving the certified message identified by the sequence number from the publisher
 10 application, to update a ledger at the subscriber application to indicate the receipt of the certified message identified by the sequence number, and to communicate a confirmation message to the publisher application, the confirmation message confirming receipt of the certified message identified by the sequence number at the subscriber application, wherein, after communicating a confirmation message to the
 15 publisher application, the certified message process is to receive a confirmation request from the publisher application, the confirmation request requesting a confirmation message from the subscriber application to confirm receipt of a certified message having a particular sequence number.

Advantages of the Invention

20 This invention has a number of advantages. For example, it provides:

Certainty

Certified delivery assures application programs that every message reaches
 each

intended recipient--in the order sent. When delivery is not possible, both senders and, optionally, listeners receive explicit information about each undelivered message.

Convenience

5 Once a program sends a certified message, the system continues delivery attempts until delivery succeeds, or until the message's time limit expires.

Control

Application programs determine an explicit time limit for each message.

10 Sending applications can disallow certified delivery to specific listening sessions.

Detail

The system can also present advisory messages to inform application programs of every significant event relating to delivery.

Process-Based or File-Based Recording

15 The system can also record the status of each message in a ledger. Applications that require certification only for the duration of the application

process can choose a process-based ledger. Applications that require certification that

20 transcends process termination and restart can choose a file-based ledger.

The invention will be described in greater detail below with reference to the accompanying drawings.

25 DESCRIPTION OF THE DRAWINGS

In the attached drawings:

Figure 1 is a schematic representation of a typical publish/subscribe environment useful for illustrating this invention; and

30 Figure 2 is a schematic representation of a typical publish/subscribe environment useful in illustrating the distributed queuing and task scheduling aspects of the invention.

SPECIFIC DESCRIPTION

OVERVIEW

Figure 1 shows a publisher application (sender) 10 and a plurality of subscriber applications (listeners) 20, 20' and 20". In the preferred embodiment of this invention the publisher and subscriber(s) are software applications based on one or more computers interconnected by a network 30 providing a data path among the applications. The publisher 10 and subscriber(s) 20 preferably implement a content-based communications protocol whereby a publisher publishes a message indicating only the content of the message and without knowing the identity or protocols used by the subscriber(s) 20. These inter-application communications are established by communications daemons 12 (associated with a publisher/sender) and 22, 22' and 22" (associated with the subscriber/listener 20, 20' and 20"). The arrangement shown in this figure is well known and described in many publications including the patents referred to above.

As is described in much greater detail below, a listener 20 can register with a specific publisher 10 to receive certified messages. This communication includes the subscribers name, its "inbox" address and the subject/content of messages it requires information on. Thus the publisher 10 will have a list of subscriber names and inboxes (but know nothing else about the subscriber) for all subscribers wishing to receive certified messages. The publisher/sender 10 will therefore expect an acknowledgement of each message it sends out; an acknowledgement it would receive from a subscriber/listener 20, 20' and/or 20". Importantly, if the publisher/sender 10 does not receive the acknowledgement, it sends an acknowledgement request message, usually for a predetermined time or number of "sends."

In the event the subscriber wishes to have guaranteed delivery of messages, the publisher can save the message to disk (or other storage) until an acknowledgement of subscriber receipt occurs. Thus, until message times out, the subscriber can, at a later date, receive the message by contacting the publisher. This would usually happen where messages are very dependent on their sequence or build upon prior message. In these circumstances missing/unreceived messages could be catastrophic. Also, in these (and in most certified messaging applications of this invention) each certified message is assigned a tracking number. This allows both sender and listener/subscriber to monitor which messages are received and/or missing.

In many applications, data communications are highly reliable, but in some situations applications require even stronger assurances of delivery. Certified delivery features offers greater certainty of delivery even in situations where processes and their network connections are unstable.

5

CERTIFIED MESSAGING

Enabling a Delivery-Tracking Session

The first step toward certified delivery is to enable a delivery-tracking session. A
10 delivery-tracking session begins as an ordinary anonymous publish/subscribe session; enabling a session adds information so that it can participate in certified delivery protocols. The additional information includes a name and a ledger.

15 Delivery-tracking sessions can send and receive messages, just as ordinary sessions can. In addition, delivery-tracking sessions can participate in certified delivery calls (that is, calls in the rvcn library layer); ordinary sessions cannot participate in these calls. (Notice the asymmetry. Delivery-tracking sessions can participate in ordinary calls, but ordinary sessions cannot participate in certified delivery calls.)

20 ***Name***

Each delivery-tracking session has a name which may be reusable, or non-reusable. The name identifies the session to other delivery-tracking sessions, and is part of the label that identifies outbound messages from the session.

25 A name is reusable when a program supplies it explicitly to the enabling call. When a session with a reusable name also has a file-based ledger, it operates as an instance of a persistent correspondent--which allows continuity of certified delivery beyond session termination and program restarts.

30 Two delivery-tracking sessions must not bind the same reusable name that is, at any moment in time, each reusable name must be unique. Sessions may reuse a name sequentially, but not simultaneously. Violating this rule can significantly obstruct certified delivery. Typically, session names have the same syntax as subject names.

Programs may omit a name in the enabling call--in which case the call generates a unique, non-reusable name for the session. No other session on any computer can ever have the same name. As a result, a session with a non-reusable name operates as a transient correspondent--no subsequent session can continue the certified delivery behavior of the session.

Enabling a delivery-tracking session creates a ledger for it. Certified delivery software uses the ledger to record information about every unresolved outbound certified message, every subject for which this session receives (inbound) certified messages, and other cooperating delivery-tracking sessions.

Programs may store the ledger in a ledger file, or in process-based storage within the running program. (Even when a session uses a ledger file, it may sometimes replicate parts of the ledger in process-based storage for efficiency; however, programmers cannot rely on this replication.)

Ledger files must be unique. That is, two sessions must not use the same ledger file (concurrently). If an operating system supports raw disk devices (also called raw partitions), a device can be specified as the ledger file.

A session with a file-based ledger and a reusable name qualifies as a persistent correspondent, with certified delivery behavior that can extend beyond session termination.

25 Labeled Messages

A labeled message is like an ordinary message, except that it includes supplementary information, which delivery-tracking sessions can use for certified message delivery:

30 The name of the delivery-tracking session that sent the message.

A sequence number assigned by the sending session.

Sending a Labeled Message

Any delivery-tracking session can send a labeled message by using the sending calls in the certified message delivery library layer. Examples of such delivery-tracking Send Calls are in the table below.

C	<code>rvcm_Send ()</code> , <code>rvcm_SendWithReply ()</code>
C++	<code>RvCmSender::certifiedSend ()</code> ,
	<code>RvCmSender::certifiedSendRequest ()</code>
Java	<code>RvCmSender.certifiedSend ()</code> , <code>RvCmSender.certifiedSendRequest ()</code>

5

Receiving a Labeled Message

For clarity, two kinds of listening endpoints are distinguished. An ordinary listener is a listener created with an ordinary listening call, such as the C functions `rv_ListenInbox ()` or `rv_ListenSubject ()`. A delivery-tracking listener is a listener created with a
 10 delivery-tracking listening call, such as the C functions `rvcm_ListenInbox ()` or `rvcm_ListenSubject ()`.

Either type of listening endpoint can receive a labeled message—delivery-tracking listeners (created by the certified delivery library), as well as ordinary listeners.

15

When an ordinary listener receives a labeled message, it presents it to the appropriate callback function as if it were an ordinary message. That is, it ignores the supplementary information that distinguishes a labeled message.

20 When a delivery-tracking listener receives a labeled message, its behavior depends on context:

If a delivery-tracking listener is registered for certified delivery, it presents the supplementary information to the callback function.

25 If a delivery-tracking listener is not registered for certified delivery, it presents a “null” sender’s name to the callback function, with a sequence number of zero.

In addition, if appropriate, the certified delivery library automatically requests that

the sender register the listener for certified delivery.

5

DISCOVERY AND REGISTRATION FOR CERTIFIED DELIVERY

Discovery

When a delivery-tracking listener receives a labeled message from a delivery-tracking sender that is not listed in the listener's ledger, the listener "discovers" the sender on the message subject.

10

Three events follow discovery:

Certified delivery software adds the sender's name to the listener's ledger, as a source of messages on the subject.

15

Certified delivery software in the listening program contacts the sending program to request registration for certified delivery of the subject and information regarding the agreement.

20

Certified delivery software presents a REGISTRATION. DISCOVERY advisory to the listening program.

25 *Registration*

When a delivery-tracking sender receives a registration request from a delivery-tracking listener, the sender automatically accepts the request. Acceptance consists of these four events:

30

Certified delivery software registers the listener for certified delivery of the subject--recording that fact in the sender's ledger.

Certified delivery software in the sending program notifies the listener session that the registration requested is accepted--the sender accepts responsibility for certified delivery on the subject.

5 Certified delivery software presents a REGISTRATION. REQUEST advisory to the sender session, informing it of the new registered listener.

10 When the certified delivery software in the listening program receives the acceptance reply, it presents a REGISTRATION CERTIFIED advisory to the listener session.

CERTIFIED DELIVERY AGREEMENT

15 Following registration and acceptance, the sender and listener have a certified delivery agreement on the subject.

20 The sender is responsible to record each outbound message on that subject, and to retain the message in its ledger until it receives confirmation of delivery from the listener (or until the time limit of the message expires).

 In return, the listener is responsible to confirm delivery of each message, and to request retransmission when a message arrives out of sequence.

25 The system arranges all of this accounting automatically. The sending and listening programs do not participate directly in these protocols--only indirectly, by sending and listening with certified delivery library calls.

30 Notice that a certified delivery agreement applies in one direction only--from a sender to a listener. A two-way conversation requires two separate certified delivery agreements.

 We refer to the two participants in a certified delivery agreement as a certified sender and a certified listener, and the labeled messages that flow between them are certified messages. Notice the subtle difference in terminology--before establishing a certified

delivery agreement, the participants are delivery-tracking senders and listeners; afterward, they are certified senders and listeners. A labeled message is only a certified message when the sender and receiver maintain a certified delivery agreement.

5 **DELIVERING A CERTIFIED MESSAGE**

Once a delivery agreement is in place, all subsequent messages on the subject (from the certified sender to the certified listener) are certified messages. Each certified message generates a series of protocol events:

10 When the system presents a certified message to the listening callback function, it includes the sequence number assigned (automatically) by the sending Software and the publisher's name.

15 When the callback function returns, certified delivery software automatically confirms delivery to the sender and records confirmation to a ledger. (Programs can override this behavior and confirm delivery explicitly.)

20 When confirmation reaches the sending program, certified delivery software records delivery in the sender's ledger, and presents a DELIVERY.CONFIRM advisory to the sender session.

25 When confirmation has arrived from every certified listener for this message, certified delivery software deletes the message from the sender's ledger, and presents a DELIVERY.COMPLETE advisory to the sender session.

Automatic Confirmation of Delivery

The default behavior of certified listeners is to automatically confirm message delivery upon return from the data callback function. Programs can selectively override this behavior for specific listening endpoints (without affecting other listening endpoints).

30 By overriding automatic confirmation, the listener assumes responsibility for explicitly confirming each inbound certified message.

Consider overriding automatic confirmation when processing inbound messages involves asynchronous activity, such as computations in other threads, database queries, or additional network communications.

5 ***Requesting Confirmation***

If a certified sender does not receive prompt confirmation of delivery from a certified listener (for example, because of network glitches), the system in the sending program automatically requests confirmation. After each request, it presents a DELIVERY.NO_RESPONSE advisory to the sending session.

10

When a listener receives a request for confirmation, it checks its ledger, and reconfirms receipt of the messages that it has already confirmed. (This behavior is identical, whether the program uses automatic confirmation, or overrides it.)

15 **SEQUENCING AND RETRANSMISSION**

A delivery-tracking sender assigns sequence numbers serially for each outbound subject, so the sequence numbers reflect the order of messages from a sender on a specific subject.

20 When certified delivery software presents certified messages to a certified listener, it preserves the sequence in which the sender sent them. If a message arrives out of sequence, certified delivery software in the listener does not present it to the callback function until all the preceding messages are available.

25 For example, a certified listener is receiving certified delivery for the subject FOO from a sender named BAZ. After receiving and presenting message number 32, the next message to arrive is message 35. Certified delivery software holds message 35 until it can first present messages 33 and 34.

30 Meanwhile, the certified delivery software in FOO requests retransmission of messages 33 and 34 from Baz. In a case where the time limit on those messages has expired--so BAZ no longer has them in its ledger--certified delivery software presents a DELIVERY.UNAVAILABLE advisory to the listener, indicating that messages 33 and 34 are no longer available. Then it presents message 35 to the data callback function.

PERSISTENT CORRESPONDENTS

We introduced the concept of persistent correspondents in the section Name, page 144.

- 5 A reusable name and a file-based ledger allow a persistent correspondent to continue certified delivery beyond the termination and restart of a session or process.

Example

- 10 Consider an example application system, in which application program JOE generates important information, and sends it to application program SUE in certified messages on the subject REMEMBER.THIS. Upon receipt, SUE stores the information in a database.

- 15 If either JOE or SUE terminate unexpectedly, it is crucial that certified messages still arrive for entry into the database. To ensure this result, both programs must represent persistent correspondents-that is, both programs enable sessions with reusable names (JOE_PC and SUE_PC), and each program keeps a file-based ledger. In addition, SUE requires old messages when it enables the session SUE_PC.

- 20 During operation, JOE has sent message number 57 on the subject REMEMBER.THIS but has not yet received delivery confirmation for messages 53- 56. SUE is processing message 53, when a sudden hardware failure causes to terminate. Meanwhile, JOE continues to send messages 58-77.

- 25 The computer restarts, and SUE restarts. The ledger file for SUE_PC indicates that message 52 was received and confirmed for the subject REMEMBER.THIS for a given publisher as JOE_PC. On restart SUE_PC will contact JOE_PC and reestablish their certified delivery agreement. When JOE accepts, JOE_PC retransmits the stored messages 53-77 on that subject.

- 30 In the above scenario it is important to notice the following:

That SUE does not miss any REMEMBER.THIS messages. However, the new SUE must gracefully fix any difficulties caused by partial processing of message 53 by the old SUE.

JOE and SUE communicate using a broadcast subject name not an inbox. Inbox names are unique, so they cannot continue beyond session termination and restart.

5 ANTICIPATING A LISTENER

In some situations, a delivery-tracking sender can anticipate the request for certified delivery from a persistent correspondent that has not yet begun listening.

10 Consider an example in which a database program (DB) records all messages with the subject STORE.THIS. The program DB enables a session that instantiates a persistent correspondent named DB_PC. All programs that send messages with the subject STORE.THIS depend on this storage mechanism.

15 One such sending program is JAN. Whenever JAN starts, it can anticipate that DB_PC will request certified delivery of the subject STORE_THIS. Suppose that JAN starts, but DB is not running, or a network disconnect has isolated JAN from DB. Anticipating that it will eventually receive a registration request for STORE.THIS from DB_PC, JAN makes an add listener call. The effect is that the software within JAN behaves as if it has a certified delivery agreement with DB_PC for the subject STORE.THIS. It stores outbound
20 messages (on that subject) in its ledger. When DB restarts, or the network reconnects, JAN automatically retransmits all the stored messages to DB.

CANCELLING CERTIFIED DELIVERY

Both listeners and senders can cancel a certified delivery agreement.

25 Listeners cancel by closing the listening endpoint, using calls listed below. Senders with certified delivery agreements to the closed endpoint receive REGISTRATION.CLOSED advisories. HOST.LISTEN.STOP advisories inform other applications of the change.

30 Senders can cancel certified delivery of a specific subject to a specific listener. The sender program deletes from its ledger all information about delivery of the subject to the listener. The sending program receives a REGISTRATION.CLOSED advisory. If the listening correspondent is available (running and reachable), it receives a

REGISTRATION.NOT_CERTIFIED advisory. (Unlike the disallow listener calls in Table 7, these calls do not cause denial of subsequent registration requests.)

DISALLOWING CERTIFIED DELIVERY

5 As described before senders automatically accept all registration requests. This is true except when the sending program explicitly disallows certified delivery to a listening session. Calls that disallow a listener cancel existing certified delivery agreements with the listener session (on all subjects), and cause certified delivery software to automatically deny subsequent registration requests from the listener session.

10

When a sender has disallowed a listener, the events connected with registration do not occur. Instead, certified delivery software in the sender notifies the listener session that the request is disallowed. When certified delivery software in the listening program receives the rejection notice, it presents a REGISTRATION.NOT_CERTIFIED advisory to the

15

Allow listener calls supersede the effect of a previous disallow listener call, allowing subsequent registration requests from the listener session to succeed.

20 NO RESPONSE TO REGISTRATION REQUESTS

It is possible that a registration request never reaches the delivery-tracking sender, or the acceptance notice never reaches the listening program (for example, because of network glitches, or termination of the sending program). After repeated attempts to register without response from the sender, certified delivery software in the listening

25

program presents a REGISTRATION.NO_RESPONSE advisory to the listening session. After several attempts to register with no response, the listener stops sending requests.

REUSABLE NAMES

Sessions that represent persistent correspondents require reusable names. Reusable

30

names must obey the syntax for subject names. Reusable names must not contain wildcard characters. Reusable names may not begin with reserved elements (such as _INBOX, _RV or _LOCAL). For best performance, reusable names should be kept short--only a few characters, typically no more than three or four elements, and no more than 50 characters in total.

LEDGER STORAGE MODE

Each delivery-tracking session records information in a ledger, which occupies storage space within the application process. A session that represents a persistent
5 correspondent must also keep a copy of the ledger in a file. The file-based ledger preserves certified delivery information beyond session (or process) termination and restart.

This feature has two associated costs:

10

The ledger file consumes disk space.

The application program pauses to update the ledger file at each significant event.

15

Transient correspondents need not pay these costs, because they do not use ledger files. However, keeping the ledger in process-based storage consumes process memory.

Ledger Size

20 The size of the ledger depends on several factors---the most important of which is the retention rate of stored data. That is, the ledger grows fastest in response to the cumulative length of incompletely delivered messages.

25 Program developers can estimate the expected size of the ledger, and must ensure that the process can allocate sufficient memory to contain it. For a file-based ledger, ensure that sufficient disk space is available as well, as memory requirements for the process application change when utilizing a file-based ledger.

EVENT MANAGER

30 The system's certified delivery depends on the event manager for timer and I/O events. When an application enables a delivery-tracking session, that session must be an event-managed session.

No Synchronous Sessions

Synchronous sessions are not valid for certified delivery calls and all delivery-tracking sessions must be asynchronous, event-managed sessions.

Distributed Queues

- 5 The system also provides use of distributed queues for one-of-n certified delivery. In particular, the system provides for distributed queueing of messages along with certified/guaranteed delivery in a "one-of-n" delivery mechanism. This delivery mechanism is illustrated in Figure 2 in which a single publisher 202 is publishing messages to three registered subscribers 204, 206 and 208 respectively. One
10 of the subscribers, 206 is a large group of n-subscribers.

- Distributed queueing addresses the problem that it is undesirable for all n-subscribers in registered subscriber 206 to get every message published by publisher 202. For example, it may be undesirable because each of the n-subscribers in group 206 will take
15 an action. In addition, if each subscriber is to receive the message (and possibly respond to it) this will consume additional network bandwidth.

- Nonetheless, it is imperative (hence the need for certified/guaranteed delivery) for at least one of the n-subscribers in group 206 to receive the message. I.e., ideally the
20 system should deliver the message to only one of the n-subscribers 206. This type of situation arises where a large number n of subscribers 206 is required to provide the desired level of fault tolerance and/or load balancing. Fault tolerance is important in situations where applications may be unstable or message delivery is absolutely critical.

- 25 In the system of the invention, each subscriber application in the group 206 operates by sending messages to another of the n-subscribers in the group 206 acting as a scheduler giving an indication of its weight. The scheduler then responds by sending the message to the particular subscriber in the group with the greatest weight. Greater details of how this is accomplished follow directly below.

- 30 Accordingly, a distributed queue of subscribing database servers 206 can accept certified messages that represent tasks (updates and queries). The system assigns each task to exactly one of the servers, while the group of servers and the distribution of tasks remains completely transparent to the client processes.

Queue Members

The member sessions of a distributed queue all share the same reusable correspondent name indicating that they are members of the queue with that name. Each member of a distributed queue listens for the same subjects--yet even when n members listen, for each inbound message (or task), only one member processes the message.

Member Roles--Worker and Scheduler

As used herein with respect to queueing and queued delivery, the terms "listener" and "worker" are used interchangeably. Each distributed queue member session can have two distinct roles--as a worker, and as a potential scheduler.

In the listener or worker role, queue member sessions support a limited subset of certified delivery calls; members can listen to a subject, override automatic confirmation of delivery and confirm delivery. Queue member sessions do not support any other certified delivery calls (in particular, calls associated with sending certified messages). However, they do support all standard calls (for example, sending ordinary messages).

The system includes fault tolerance software that maintains exactly one active scheduler in each queue; if the scheduler process terminates, another member assumes the role of scheduler. The queue member session in the scheduler role assigns inbound tasks to listeners in the queue. (A scheduler can assign tasks to its own listener component, but only does so when all other listeners are busy.)

The Scheduler as a Fault-Tolerant Component

Although any queue member has the potential to become the scheduler, fault tolerance software maintains exactly one scheduler at all times. Fault tolerance parameters guide the software to select the most suited member as scheduler.

Scheduler weight represents the ability of a member session to fulfill the role of scheduler, relative to other members of the same queue, i.e., the greatest availability or unused member resources. The queue members use relative scheduler weight values to

elect one member as the scheduler; members with higher scheduler weight take precedence.

5 The active scheduler sends heartbeat messages at the interval specified by the user. Heartbeat messages inform other members that a member is acting as the scheduler. All sessions in the queue must specify the same scheduler heartbeat interval.

10 In addition, all sessions in the queue must specify the same scheduler activation interval. When the heartbeat signal from the scheduler has been silent for this interval the queue member with the greatest scheduler weight takes its place as the new scheduler.

Assigning Tasks to Workers

15 The scheduler assigns each task to a worker or listener (another queue member session). That worker or listener alone processes the task message in a data callback function.

Worker Weight

20 Relative worker or listener weights assist the scheduler in assigning tasks. When the scheduler receives a task, it assigns the task to the available worker or listener with the greatest worker or listener weight.

25 Enabling a session as a queue member tacitly sets its worker or listener weight parameter to 1. That is, all members implicitly have the same worker or listener weight, unless program code explicitly changes the worker or listener weight.

Availability

30 When the scheduler receives a task, it assigns the task to the available worker listener with the greatest listener weight.

A worker listener is considered available unless either of these conditions are true:

The pending tasks assigned to the worker or listener exceed its task capacity.

The worker or listener session is the scheduler. (The scheduler assigns tasks to its own worker or listener only when all other workers or listeners are busy.)

Task Capacity

Task capacity is the maximum number of tasks that a worker or listener can accept. When the number of accepted tasks reaches this maximum, the worker or listener cannot accept additional tasks until it completes one or more of them.

When the scheduler receives a task, it assigns the task to the worker or listener with the greatest worker or listener weight--unless the pending tasks assigned to that worker or listener exceed its task capacity. When the preferred worker or listener has too many tasks, the scheduler assigns the new inbound task to the worker or listener with the next greatest worker or listener weight.

Enabling a session as a queue member tacitly sets its worker or listener task capacity to 1. Programmers can tune task capacity based on two factors:

Multi-tasking program on multiprocessing hardware.

On a multiprocessing computer, a multi-threaded program that devotes n threads and n processors to inbound tasks has task capacity n .

Communication time lag.

In most distributed queue applications, the communication time is an insignificant fraction of the task turnaround time. That is, the time required to assign a task and signal its completion is very small compared to the time required to process the task itself. For example, when average task turnaround time is 2000 milliseconds, of which communication time contributes only 10 milliseconds to the total, then task capacity is the same as the number of processors or threads.

However, in some situations communication time can be significant--for example, when the queue members are distributed at distant sites connected by a WAN. When communication time is significant, the meaning of task capacity changes; instead of signifying the number of tasks that a listener can process concurrently, it signifies the

number of tasks that can fill the listener's capacity despite the communication time lag. For example, when the average task turnaround time is 1500 milliseconds, of which the average task processing time contributes 1000 milliseconds to the total, then setting the task capacity to 3 minimizes the listener's idle time between tasks.

- 5 When tuning task capacity to compensate for communication time lag, balance is critical. Underloading a listener (by setting its tasks capacity too low) can cause the listener to remain idle while it waits for the schedule to assign its next task. Conversely, overloading a listener (by setting its task capacity too high) can cause some assigned tasks to wait, while other listeners that might have accepted those tasks
10 remain idle.

TASK SCHEDULING

- In a further application of this invention, the broad concepts of distributed queuing can be applied to scheduling tasks for different task doing applications. In this
15 application an application can be either a scheduler or a worker or both. Each worker is assigned a weight indicating its ability to do work, usually the number of tasks it can do simultaneously. Typically, workers assign their own weights.

- One application/member of a group becomes the scheduler. Once this occurs, all other
20 applications become designated workers only. The scheduler becomes both a worker and the scheduler.

- When a task is received by the group (the scheduler) it assigns the task to the worker with the highest "weight" or ability to do tasks. The worker then calls back to the
25 scheduler accepting the task and, upon completion, returns a call to the scheduler indicating this fact. In certain instances, the call back to the scheduler includes both an acceptance and a notification of task completion.

- Two Appendices, A and B are attached. These appendices include detailed C coding
30 information respectively for Certified messaging and for message queuing.

The invention now being fully described, it will be apparent to one of ordinary skill in the art that many changes and modifications can be made thereto without departing from its spirit or scope.

Appendix A: Certified Message Delivery (Programming Details for C Programmers)

5 As indicated previously, even though some communications are highly reliable, certain applications require even stronger assurances of delivery. Certified delivery features offers greater certainty of delivery even in situations where processes and their network connections are unstable.

10 This Appendix A provides programming details for C programmers wishing to implement Certified message Delivery. The Appendix provides, in Table A1, an overview listing of Certified's messaging Deliver Datatypes and Functions. Each Datatype or Function is then described in greater detail with Cross-references to related Datatypes or Functions.

15

Certified Message Delivery CAPI

The following table summarizes the datatypes and functions in the certified message delivery C API.

20

Table A1: Certified Message Delivery: Datatypes and Functions

Item	Description
<code>rvcm_Enable()</code>	Enable an existing session for delivery tracking.
<code>rvcm_ListenSubject()</code>	Listen for broadcast messages, and request certified delivery whenever available.
<code>rvcm_ListenInbox()</code>	Open a delivery-tracking inbox to listen for point-to-point messages, and request certified delivery whenever available.
<code>rvcm_Callback</code>	Function type of callback functions that receive and process inbound messages for delivery-tracking listeners.
<code>rvcm_ListenId</code>	Certified listening calls return identifiers of this type.
<code>rvcm_seq</code>	Certified messages bear sequence numbers of this type.
<code>rvcm_close()</code>	Close a delivery-tracking endpoint; stop listening for messages on it.
<code>rvcm_Send()</code>	Send a labeled message, and track delivery to cooperating listeners.
<code>rvcm_SendWithReply()</code>	Send a labeled request message, and track delivery to cooperating listeners.
<code>rvcm_AddListener()</code>	Pre-register an anticipated listener.

Table A1: Certified Message Delivery: Datatypes and Functions (con't.)

Item	Description
<code>rvcm_RemoveListener()</code>	Cancel certified delivery of a subject to a listening correspondent.
<code>rvcm_DisallowListener()</code>	Cancel certified delivery of all subjects to a listening correspondent, and deny subsequent registration requests.
<code>rvcm_AllowListener()</code>	Invite a receiver to reinstate certified delivery for its listeners.
<code>rvcm_NoAutoConfirm()</code>	Override automatic confirmation of delivery.
<code>rvcm_confirm()</code>	Confirm delivery of a certified message.
<code>rvcm_ReviewLedger()</code>	Summarize the delivery status of messages in the ledger,
<code>rvcm_ReviewCallback</code>	Function type of callback functions that process ledger information for <code>rvcm_ReviewLedger()</code> .
<code>rvcm_SyncLedgerFile()</code>	Synchronize the ledger file.
<code>rvcm_Error</code>	Datatype. Enumerates error codes for the certified message delivery API.
<code>rvcm_ErrorText()</code>	Return a text string describing an error code.

rvcm_Enable()*Function***Declaration**

```

5  rvcm_Error rvcm_Enable (
        rv_Session    session,
        rv_Name       name,
        rv_Name       reserved,
        char*         ledgerFile,
10         rv_Boolean  requireOldMsgs

```

Purpose

Enable an existing session for delivery tracking.

15

Remarks

All other rvcm functions require an enabled session as an argument. Programs must call rvcm_Enable () before any other calls related to certified delivery.

20

A user can use an enabled session for both certified and non-certified communications. For example, an enabled session supports calls to rvcm_Send () and rv_Send ().

25 Once a session is enabled for certified delivery, it remains enabled until terminated with rv_Term (). The user cannot subsequently change the certified delivery parameters of the session.

Name

30 rvcm_Enable () promotes its session argument to a delivery-tracking session.

If name is NULL, then rvcm_Enable () generates a unique, non-reusable name for this session.

If name is non-NULL, then the session binds that name. A correspondent can persist beyond session termination only when it has both a reusable name and a file-based ledger.

5 Ledger File

Every delivery-tracking session stores the state of its certified communications in a ledger, which is stored in memory associated with the process.

- 10 If ledgerFile is NULL, then this session uses a only process-based ledger. When the session or process terminates, all information in the ledger is lost.

- 15 If ledgerFile specifies a valid file name, then this session uses that file for ledger storage. If the session or process terminates with incomplete certified communications, the ledger file records that state. When a new session binds the same reusable name, it reads the ledger file and continues certified communications from the state stored in the file.

- 20 Even though a session uses a ledger file, it may sometimes replicate parts of the ledger in process-based storage for efficiency; however, programmers cannot rely on this replication.

- If the operating system supports raw storage devices (also called raw partitions), the user can specify such a device as the ledger file.

25

An optional prefix determines whether writing to the ledger file is a synchronous operation:

- 30 ■ To specify synchronous writing (the default), either supply an ordinary file name, or prepend the string sync* to the file name; for example, "myLedger" (implicit) or "sync*/local/myLedger" (explicit). Each time a ledger item is written, the call does not return until the data is safely stored in the file system.

- To specify asynchronous writing, prepend the string nosync* to the file name; for example, "nosync*/local/myLedger". The ledger file might not accurately reflect program state in cases of hardware or operating system kernel failure.

5 A program that uses an asynchronous ledger file can explicitly synchronize it by calling rvcm_SyncLedgerFile(), described below.

Parameters

10

Parameter	Description
session	Enable this session for certified delivery tracking.
name	<p>Bind this reusable name to the session, so the session represents a persistent correspondent with this name.</p> <p>If non-Null, the name must conform to the syntax rules for subject names. It cannot begin with reserved tokens. It cannot be a non-reusable name generated by another call to rvcm_Enable().</p> <p>If this argument is NULL, then rvcm_Enable() generates a unique, non-reusable name for the duration of the session.</p>
reserved	This parameter is reserved for future enhancement. The user must supply NULL for foilNard compatibility.

Parameter	Description
ledgerFile	<p>If this argument is non-NULL, then this session uses a file-based ledger. The argument must represent a valid file name. Actual locations corresponding to relative file names conform to operating system conventions.</p> <p>Prepending nosync* to the file name specifies asynchronous output to the file system. sync* or no prefix specifies synchronous output (flushed before each output call returns).</p> <p>If this argument is NULL, then this session uses a process-based ledger.</p>
requireOldMsgs	<p>This parameter indicates whether a persistent correspondent requires delivery of messages sent to a previous session with the same name, for which delivery was not confirmed. Its value affects the behavior of other delivery-tracking senders.</p> <p>If this parameter is RV_TRUE and name is non-NULL, then this session requires certified senders to retain unacknowledged messages sent to this persistent correspondent. When this session begins listening to the appropriate subjects, the senders can complete delivery. (It is an error to supply RV_TRUE when name is NULL.)</p> <p>If this parameter is RV_FkLSr., then this session does not require certified senders to retain unacknowledged messages. Certified senders may delete those messages from their ledgers.</p>

WO 99/09490

PCT/US98/17115

Errors

RVCM Error Code	Indicates
RVCM_OK	No error. The call completed successfully.
RVCM_ERR_INVALID_SESSION	The function received a session argument that is not a valid rv_session (for example, NULL, or a session that has already terminated).
RVCM_ERR_BAD_SESSION_NAME	The function received an ill-formed reusable name.
RVCM_ERR_NO_MEMORY	The function could not complete because the operating system denied its request to allocate storage.
RVCM_ERR_FILE_IO_ERROR	rvcm_Enable () encountered an error while opening the ledger file. For example, an explicitly named directory does not exist.
RVCM_ERR_FILE_NO_PERMISSION	File privileges are insufficient for rvcm_Enable () to open the ledger file.
RVCM_ERR_LEDGER_NAME_CONFLICT	rvcm_Enable () received NULL as the name parameter, but a non-NULL value as the ledgerFile parameter.
RVCM_ERR_PARAMETER_CONFLICT	<p>The function received conflicting values for parameters.</p> <p>rvcm_Enable () received RV_FALSE as its requireOldMsgs parameter, and NULL as its name parameter. A non-reusable name implies a transient correspondent, which cannot have backlog messages.</p>

RVCM Error Code	Indicates
RVCM_ERR_FILE_NOT_LEDGER_OWNER	The reusable name recorded in the file differs from the name of this session. <code>rvcm_Enable ()</code> stopped reading the file.
RVCM_ERR_CORRUPT_LEDGER_FILE	The ledger file is corrupt. <code>rvcm_Enable ()</code> could read only part of the ledger file into process-based memory. Some information may be lost.
RVCM_ERR_SESSION_ALREADY_ENABLED	<code>rvcm_Enable ()</code> received a session that is already enabled for delivery tracking. It is illegal to enable a session more than once.

Coding Example

```

5  cm_err = rvcm_Enable(sess, "CM_EXAMPLE", NULL,
                        "my_ledger_file", RV_TRUE);

```

```

    if (cm_err != RVCM_OK)
    {
10      fprintf(stderr, 'Can't enable CM session--%s\n',
                rvcm_ErrorText (sess, cm_err) );
        exit (-1);
    }

```

15 See Also

`rvcm_SyncLedgerFile()`, below

20 `rvcm_ListenSubject()`

Function

Declaration

```

rvcm_Error rvcm_ListenSubject (
    rv_Session      session,
5    rvcm_LisCenId* listenid,
    rv_Name         subject,
    rvcm_Callback   dataCallbackFn,
    rv_Opaque       closureArg )

```

10 Purpose

Begin listening for messages that match the subject, and request certified delivery whenever available. Whenever a message arrives, the callback function receives it.

15 Remarks

This function is parallel to `rv_ListenSubject ()`--it creates an endpoint to receive messages with matching subjects. The endpoint receives both labeled messages and ordinary messages.

20

When a labeled message arrives from an unfamiliar delivery-tracking session, the receiving session requests certified delivery for the subject. If the sending session accepts the request, then the two sessions cooperate to certify delivery of subsequent messages with this subject.

25

Unlike ordinary listening endpoints, the user cannot maintain more than one delivery-tracking listening endpoint per subject. When one endpoint is already open, subsequent calls to `rvcm_ListenSubject()` with the same subject return an error. (This restriction applies to each delivery-tracking session; however, a program with several
30 delivery-tracking sessions can open independent delivery-tracking listeners with identical subjects.)

Unlike `rv_ListenSubject()`, the user cannot use `rvcm_ListenSubject()` to listen to wildcard subjects.

The software automatically confirms message delivery when the data callback function returns.

5

Parameters

Parameter	Description
session	A delivery-tracking session.
listenId	When <code>rvcm_ListenSubject()</code> returns (without error), this location contains a handle denoting the new endpoint. To stop listening on the subject, pass this handle to <code>rvcm_Close()</code> .
subject	Listen for messages with this subject name. Wildcard subjects are illegal.
dataCallbackFn	When a message arrives, pass it to this callback function.
closureArg	Pass this closure argument to the callback function. This argument must be a pointer, but it can point to any type of data. It contains any information needed by the callback function. This argument is treated as an opaque closure, forwarding it to the callback function without accessing its value.

Errors

RVCM_ERR Code	Indicates
RVCM_OK	No error. The call completed successfully.
RVCM_ERR_INVALID_SESSION	The function received a session argument that is not a valid rv_session (for example, NULL, or a session that has already terminated).
RVCM_ERR_BAD_ARG	The function received an illegal argument. rvcm_ListenSubject() received either a NULL callback function, or a NULL listenid pointer.
RVCM_ERR_NO_MEMORY	The function could not complete because the operating system denied its request to allocate storage.
RVCM_ERR_BAD_SUBJECT	rvcm_ListenSubject() received an ill-formed subject name. Either it is NULL, or contained too many total characters, too many characters in an element, too many elements, a wildcard character, or an illegal prefix.
RVCM_ERR_DUPLICATE_SUBJECT	rvcm_ListenSubject() Can maintain at most one open listening endpoint per subject (per session); it cannot open a second listening endpoint for this subject.
RVCM_ERR_SESSION_NOT_ENABLED	The function received a session that is not enabled for delivery tracking.

Coding Example

```

cm_err = rvcm_ListenSubject(sess, &listenId, subject,
                           CM_callback, myClosure);
if (cm_err != RVCM_OK)
5      fprintf(stderr, "error %s listening to \"%s\"\n",
              rvcm_ErrorText (sess, cm_err), subject);

```

See Also

```

10  rvcm_Callback;
    rvcm_ListenId;
    rvcm_ListenInbox();
    rvcm_Close(), all described below

```

```

15
    rvcm_ListenInbox()

```

Function

```

20  rvcm_Error rvcm_ListenInbox (

        rv_Session      session,
        rvcm_ListenId*  listenid,
        rv_Name          inbox,
25  rv_Size              inboxLimit,
        rvcm_Callback    dataCallbackFn,
        rv_Opaque        closureArg)

```

Purpose

```

30  Open an inbox and begin listening for point-to-point messages addressed to it.
    Request certified delivery whenever available. Whenever a message arrives, pass it to
    the callback function.

```

Remarks

This function is parallel to *rv_ListenInbox ()*--it creates an inbox to receive point-to-point messages. The inbox receives both labeled messages and ordinary messages.

- 5 When a labeled message arrives from an unfamiliar delivery-tracking session, the receiving session requests certified delivery for the inbox name. If the sending session accepts the request, then the two sessions cooperate to certify delivery of subsequent messages to this inbox.

- 10 Certified delivery to an inbox is limited to the duration of the inbox. Once the users closes an inbox or terminates its session, the inbox and its name become obsolete; the user can never open another inbox with the same name. Since the system can never complete delivery of messages addressed to an obsolete inbox, it automatically deletes stored messages when it detects that an inbox has become obsolete.

- 15 The system automatically confirms message delivery when the data callback function returns.

Parameters

Parameter	Description
session	A delivery-tracking session.
listenId	When <i>rvcm_ListenInbox ()</i> returns (without error), this location contains a handle denoting the new inbox. To stop listening, pass this handle to <i>rvcm_Close ()</i> .
inbox	Location to store the generated name of the new inbox. The allocated space must be at least <i>RV_t,mX_INBOX_NAME</i> (currently 100 bytes).
inboxLimit	Number of bytes allocated to store the new inbox name.
dataCallbackFn	When a message arrives, pass it to this callback function.

Parameter	Description
closureArg	Pass this closure argument to the callback function. This argument must be a pointer, but it can point to any type of data. It contains any information needed by the callback function. the system treats this argument as an opaque closure, forwarding it to the callback function without accessing its value.

Errors

RVCM_ERR Code	Indicates
RVCM_OK	No error. The call completed successfully
RVCM_ERR_INVALID_SESSION	The function received a session argument that is not a valid rv_session (for example, NULL, or a session that has already terminated).
RVCM_ERR_BAD_ARG	The function received an illegal argument. rvcm_ListenInbox () received either a NULL inbox name pointer, a NULL callback function, or a NULL listenid pointer.
RVCM_ERR_NO_MEMORY	The function could not complete because the operating system denied its request to allocate storage.
RVCM_ERR_SESSION_NOT_ENABLED	The function received a session that is not enabled for delivery tracking.

5

Coding Example

```
char inboxName [RV_MAX_INBOX_NAME];
```

```
cm_err = rvcm_ListenInbox(sess, &listenId, inboxName, sizeof(inboxName),
                          CM_callback, myClosure);
```

```
5      if (cm_err != RVCM_OK)
          fprintf(stderr, "error %s listening to certified inbox.\n",
                  rvcm_ErrorText(sess, cm_err));
```

See Also,

```
10  rvcm_Callback, below
    rvcm_ListenId, below
    rvcm_ListenSubject(), above
    rvcm_Close(), below.
```

15

rvcm_Callback

Datatype

20 **Declaration**

```
void* rvcm_Callback (
    rv_Session      session,
    rv_Name         subject,
    rv_Name         replyName
25  rvmsg_Type      msgType,
    rvmsg_Size      msgSize,
    rvmsgData       msg,
    rvcm_Seq        sequenceNum,
    rv_Name         senderName,
30  rv_Opaque       closureArg )
```

Purpose

`rvcm_Callback` is the function type of data callback functions to delivery-tracking listeners. Applications define functions of this type to receive inbound messages and take appropriate actions.

5 **Remarks**

This function type is parallel to `rv_Callback`. Notice that its function signature includes two additional parameters, `senderName` and `sequenceNum`, to receive the tracking data that labels the inbound message. Application programs can use these arguments for testing and auditing.

10

The system automatically confirms message delivery when the data callback function returns.

15 The user can write several callback functions to process the various kinds of messages that the application expects to receive. The user can use the same callback function to process messages at several endpoints. Callback functions can take any action in processing a message, except for the following restrictions:

20 ■ Callback functions must not attempt to modify the data (the values of the parameters `msg`, `subject`, `reillyName` and `senderName`) in any manner. The callback function receives data through pointers; the actual data resides in memory that does not belong to the application. The data pointers remain valid only until the callback function returns.

25 ■ The data callback functions must return promptly.

Parameters

Parameter	Description
session	This parameter receives the current session.
subject	<p>This parameter receives the destination subject name of the inbound message.</p> <p>Do not modify this value. This pointer remains valid only until the callback function returns.</p>
replyName	<p>If the inbound message carries a name for replies, this parameter receives it. Otherwise NULL.</p> <p>Do not modify this value. This pointer remains valid only until the callback function returns.</p>
msgType	This parameter receives the datatype of the message.
msgSize	This parameter receives the size (in bytes) of the message.
msg	<p>This parameter receives a pointer to the message data.</p> <p>Do not modify this value. This pointer remains valid only until the callback function returns.</p>
sequenceNum	If the message is certified, this parameter receives the sequence number that the sender assigned to the message. Otherwise, this parameter receives zero.
senderName	<p>If the message is labeled, this parameter receives the name of the delivery-tracking session that sent the message. Otherwise, this parameter receives NULL.</p> <p>Do not modify this value. This pointer remains valid only until the callback function returns.</p>

closureArg	This parameter receives a closure argument supplied by the application when it began listening. This argument is a pointer, but it can point to any type of data. It contains any information needed by the callback function. the system treats this argument as an opaque closure, forwarding it to the callback function without accessing its value.
------------	--

Coding Example

- 5 This example code illustrates a data callback function for receiving messages with certified delivery.

```

void
CM-callback (
10     rv_Session session,
        rv_Name subject,
        rv_Name replyName,
        rvmsg_Type msgType,
        rvmsg_Size msgSize,
15     rvmsg_Data msg,
        rvcm_Seq seqNumber,
        rv_Name sender,
        rv_Opaque myClosureArg )
{
20
    printf("Received: subject=%s, reply=%s. message=",
           subject, (replyName!=NULL ? replyName : "<none>"));
    rvmsg_PrintItem(session, msgType, msgSize, msg, NULL);
    printf("\n");
25    printf(" sequence number=%ld, sender=%s\n",
           seqNumber, (sender!=NULL ? sender : "<none>"));

```



```
fflush(stderr);
```

See Also

5

rvcm_ListenId; rvcm_Seq; and rvcm_Close(), below.

rvcm_ListenId

10

*Datatype***Declaration**

```
typedef void* rvcm_ListenId;
```

15

Purpose

The rvcm_ListenSubject () and rvcm_ListenInbox () functions return a handle of type rvcm_ListenId. To stop listening for the corresponding information, pass this handle to rvcm_Close ().

20

Remarks

an rvcm_ListenId is not meaningful outside of the session in which it was created. Each rvcm_ListenId is a unique handle representing an association between a subject and a callback function. Use rvcm_ListenId only within the local program that receives it from one of the listening functions, and treat it as opaque.

25

rvcm_Seq*Datatype*

30

Declaration

```
typedef unsigned long rvcm_Seq;
```

Purpose :

Sequence number of a labeled message.

Remarks

- 5 Sequence numbers are limited to 32 bits on all platforms (even platforms that support 64-bit integers).

rvcm_Close()

10 Function

Declaration

- ```
rvcm_Error rvcm_Close (
 rv_Session session,
15 rvcm_ListenId listenid
```

#### Purpose

Close a delivery-tracking endpoint; stop listening for messages on it.

#### 20 Remarks

This function is parallel to rv\_Close ().

Cooperating senders receive a REGISTRATION. CLOSED advisory, indicating that the delivery tracking agreement is no longer in effect. Senders receive a DELIVERY.

- 25 FAILED advisory for each undelivered message to the closed endpoint, and the system removes undelivered messages from the sender's ledger.

The system deletes the listener's ledger items corresponding to the closed subject.

- 30 When rvcm\_Close ( ) closes an endpoint, it generates a HOST.LISTEN.STOP advisory message to inform other applications that this application has stopped listening to the subject.

It is important that a persistent listener close a delivery-tracking endpoint when it no longer requires certified delivery of the corresponding subject--and only then. Open endpoints cause certified senders to store messages in the ledger while awaiting delivery confirmation from the sender. From the sender's perspective, a persistent listener that exits without closing its listening endpoints appears the same as a listener that terminates abnormally; the sender continues to store messages awaiting the return of the Listener process. Once an endpoint is closed, senders do not store certified messages for that listener, and successive listener processes with the same correspondent name do not receive certified delivery of messages sent in the interim.

10

### Coding Example

Close endpoints when the application is finished receiving data. Closing endpoints lets TiB/Rendezvous software re-use the associated storage resources. After closing an endpoint, delete all references to it, to guard against closing it twice.

15

It is illegal to close the same endpoint more than once. On some platforms, the error `RVCM_ERR_NONEXISTENT_ID` results; on other platforms, the result can be a fatal error

20

(because it references dynamically allocated memory that has been freed).

This code fragment illustrates the recommended idiom for closing endpoints:

```
if (foo->listenId != NULL)
25 (rvclm_Close(foo->listenId);
 foo->listenId = NULL;)
```

**Parameters**

| Parameter | Description                                              |
|-----------|----------------------------------------------------------|
| session   | The delivery-tracking session that created the endpoint. |
| listenId  | Close the endpoint that this handle denotes.             |

**Errors**

| RVCM_ERR Code                | Indicates                                                                                                                                                                          |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_OK                      | No error. The call completed successfully.                                                                                                                                         |
| RVCM_ERR_INVALID_SESSION     | The function received a session argument that is not a valid rv_Session (for example, NULL, or a session that has already terminated).                                             |
| RVCM_ERR_BAD_ARG             | The function received an illegal argument. rvcm_Close() received a NULL listenId pointer.                                                                                          |
| RVCM_ERR_NONEXISTENT_ID      | rvcm_Close () received a NULL listenId pointer either it is NULL, or it points to something other than an rvcm_ListenId, or it points to an endpoint that has already been closed. |
| RVCM_ERR_NO_MEMORY           | The function could not complete because the operating system denied its request to allocate storage.                                                                               |
| RVCM_ERR_SESSION_NOT_ENABLED | The function received a session that is not enabled for delivery tracking.                                                                                                         |

5

WO 99/09490

PCT/US98/17115

**See Also**

rvcm\_ListenId, above.

rvcm\_Send()

**5 Function****Declaration**

```

rvcm_Error rvcm_Send (
 rv_Session session,
10 rv_Name subject,
 rvmsg_Type msgType,
 rvmsg_Size msgSize,
 rvmsg_Data msg,
 unsigned long timeLimit,
15 rvcm_Seq* sequenceNum)

```

**Purpose**

Send a labeled message, and track delivery to cooperating listeners.

**20 Remarks**

This function is parallel to rv\_Send (). Notice that its signature includes two additional parameters, timeLimit and SequenceNum.

Use timeLimit to specify the duration of the message (in seconds). The system retains  
25 the message in its ledger until either it receives delivery confirmation from all cooperating listeners, or the timeLimit expires. If the time limit expires before delivery is complete, the system removes the message from the ledger, and generates a DELIVERY. FAILED advisory message listing the cooperating listeners that did not confirm delivery of the message.

30

We recommend a timeLimit value greater than 60 seconds, since the domain holds messages for 60 seconds.

`rvcm_Send ( )` labels the message with the name of the delivery-tracking session and a sequence-number. `rvcm_Send ( )` passes the sequence number back to the caller in its `sequenceNum` parameter (the user can use this number for auditing).

- 5 Each sending session maintains a separate sequence for each subject it sends. As a result, receivers can uniquely identify each labeled message by the three data callback arguments `subject`, `senderName` and `sequenceNum`.

- 10 When `msg` has self-evident length, the user may supply zero for `msgSize` (the system computes the actual size automatically). Types with self-evident size are `RVMSG_RVMSG`, `RVMSG_STRING` (when the string is NULL-terminated) and `RVMSG_ENCRYPTED`. All other types require an explicit size argument in this call.

- 15 `rvcm_Send()`

`rvcm_Send ( )` copies its arguments. After `rvcm_Send ( )` returns, the user may free or reuse the storage (for example, a message buffer).

## 20 Warning

It is illegal to send messages to wildcard subject names. Although `rvcm_Send ( )` does not prevent the user from sending illegally to wildcard subjects, the results are unpredictable.

## 25 Parameters

| Parameter            | Description                                     |
|----------------------|-------------------------------------------------|
| <code>session</code> | A delivery-tracking session.                    |
| <code>subject</code> | Send the message to this subject name or inbox. |
| <code>msgType</code> | Datatype of the message data.                   |

|             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| msgSize     | Length of the data (in bytes).                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| msg         | Location of the data to send.                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| timeLimit   | <p>Retain the message in the ledger, and continue attempts at delivery either until completion of delivery or until this time limit (in seconds) expires.</p> <p>Zero is a special value, indicating no time limit; the message remains in the ledger until delivery is complete to all certified listeners.</p> <p>A non-zero value less than 60 seconds adds no advantage over ordinary reliable message delivery, since rvd retains and retransmits messages for 60 seconds.</p> |
| sequenceNum | This location receives the sequence number of this message.                                                                                                                                                                                                                                                                                                                                                                                                                         |

**Errors**

| RVCN_ERR Code | Indicates                                  |
|---------------|--------------------------------------------|
| RVCN_OK       | No error. The call completed successfully. |

|                          |                                                                                                                                                                                           |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_ERR_INVALID_SESSION | The function received a session argument that is not a valid rv_Session (for example, NULL, or a session that has already terminated).                                                    |
| RVCM_ERR_BAD_ARG         | The function received an illegal argument. rvcm_Send () or rvcm_SendWithReply () received either a NULL subject, or a NULL sequence number pointer                                        |
| RVCM_ERR_NO_MEMORY       | The function could not complete because the operating system denied its request to allocate storage.                                                                                      |
| RVCM_ERR_BAD_SUBJECT     | rvcm_Send () or rvcm_SendWithReply () received an ill-formed subject name.<br><br>Either it contained too many total characters, too many characters in an element, or too many elements. |



RVCM\_ERR\_SESSION\_NOT\_ENABLED

The function received a session that is not enabled for delivery tracking.

**Coding Example**

```

int time_limit = 600; /* 600sec = 10min */
5
cm_err = rvcm_Send(sess, subject, type, sizeof(msg), msg,
 time_limit, &seq_no);
if (cm_err == RVCM_OK)
 fprintf(stderr, "Sent sequence num %d\n", seq_no);
10 else
 fprintf(stderr, "Error while sending certified message: %s\n",
 rvcm_ErrorText (sess, cm_err));

```

**See Also**

```

15 rvcm_Seq, above
rvcm_SendWithReply(), below.
rvcm_SendWithReply()

```

**Function**

20

**Declaration**

```

rvcm_Error rvcm_SendWithReply (
 rv_Session session,
 rv_Name subject,
25 rv_Name replyName,
 rvmsg_Type msgType,
 rvmsg_Size msgSize,
 rvmsg_Data msg,
 unsigned long timeLimit,

```

rvcm\_Seq\*

sequenceNum

**Purpose**

Send a labeled request message, and track delivery to cooperating listeners. A request  
 5 message includes a reply name as a return address for response messages.

**Remarks**

This function is parallel to rv\_SendWithReply (). Notice that its signature includes  
 two additional parameters, timeLimit and sequenceNum.

10

The reply name must be the subject name of an open listening endpoint (either  
 broadcast or inbox). An application may receive zero, one or several responses to a  
 request message. Before the user calls rvcm\_SendWithReply ( ) the user must ensure  
 that the appropriate application components are listening to the reply name.

15

rvcm\_SendWithReply ( ) is a non-blocking function. It returns immediately, and the  
 callback function receives any replies asynchronously. A reply is not guaranteed (for  
 example, if the receiver does not send any reply).

20

Use timeLimit to specify the duration of the message. the system retains the message  
 in its ledger until either it receives delivery confirmation from all cooperating  
 listeners, or the timeLimit expires. If the time limit expires before delivery is  
 complete, the system removes the message from the ledger, and generates a  
 DELIVERY.FAILED advisory message listing the cooperating listeners that did not  
 25 confirm delivery of the message.

A timeLimit value greater than 60 seconds is recommended, since the domain holds  
 messages for 60 seconds.

30

*rvcrn\_Send WithReply()*

rvcm\_SendWithReply() labels the message with the name of the delivery-tracking  
 session and a sequence number. rvcm\_SendWithReply() passes the sequence number

WO 99/09490

PCT/US99/17115

back to the caller in its sequenceNum parameter (the user can use this number for auditing).

Each sending session maintains a separate sequence for each subject it sends. As a result, receivers can uniquely identify each labeled message by the three data callback arguments subject, senderName and sequenceNum.

When msg has self-evident length, the user may supply zero for msgSize (the system computes the actual size automatically). Types with self-evident size are RVMSG\_RVMSG, RVMSG\_STRING (when the string is NULL-terminated) and RVMSG\_ENNCRYPTED. All other types require an explicit size argument in this call.

rvcm\_SendWithReply() copies its arguments. After rvcm\_SendWithReply() returns, the user may free or reuse the storage (for example, a message buffer).

#### Warning

It is illegal to send messages to wildcard subject names. Although the function rvcm\_SendWithReply() does not prevent the user from sending illegally to wildcard subjects, the results are unpredictable.

#### Parameters

| Parameter | Description                                     |
|-----------|-------------------------------------------------|
| Session   | A delivery-tracking session.                    |
| Subject   | Send the message to this subject name or inbox. |

|             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ReplyName   | <p>Subject name for replies to this request message (similar to a return address on a letter, and delivered to receiving applications in the replyName argument of the callback function).</p> <p>The reply name may be an inbox or subject name. Before calling rvcn_SendWithReply(), ensure that a listening endpoint is already open for the reply name.</p>                                                                                                                     |
| MsgType     | Datatype of the message data.                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| MsgSize     | Length of the data (in bytes).                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Msg         | Location of the data to send.                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| timeLimit   | <p>Retain the message in the ledger, and continue attempts at delivery either until completion of delivery or until this time limit (in seconds) expires.</p> <p>Zero is a special value, indicating no time limit; the message remains in the ledger until delivery is complete to all certified listeners.</p> <p>A non-zero value less than 60 seconds adds no advantage over ordinary reliable message delivery, since rvd retains and retransmits messages for 60 seconds.</p> |
| sequenceNum | This location receives the sequence number of this message.                                                                                                                                                                                                                                                                                                                                                                                                                         |

**Errors**

| RVCM_ERR Code                | Indicates                                                                                                                                                                        |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_OK                      | No error. The call completed successfully.                                                                                                                                       |
| RVCM_ERR_INVALID_SESSION     | The function received a session argument that is not a valid rv_Session (for example, NULL, or a session that has already terminated).                                           |
| RVCM_ERR_BAD_ARG             | The function received an illegal argument. rvcm_Send() or rvcm_SendWithReply() received either a NULL subject, or a NULL sequence number pointer.                                |
| RVCM_ERR_NO_MEMORY           | The function could not complete because the operating system denied its request to allocate storage.                                                                             |
| RVCM_ERR_BAD_SUBJECT         | rvcm_Send() or rvcm_SendWithReply() received an ill-formed subject name. Either it contained too many total characters, too many characters in an element, or too many elements. |
| RVCM_ERR_SESSION_NOT_ENABLED | The function received a session that is not enabled for delivery tracking.                                                                                                       |

**Coding Example**

```

cm_err = rvcm_SendWithReply(sess, subject, reply,
5 type, sizeof(msg), msg,
 600, &seq_no);

(cm_err == RVCM_OK)
 fprintf(stderr, "Sent sequence num %d\n", seq_no);
else
10 fprintf(stderr, "Error while sending certified message: %s\n",
 rvcm_ErrorText (sess, cm_err));

```

**See Also ~**

rvcm\_Seq, page 203; and  
rvcm\_SendWithReply(), above.

5

**rvcm\_Add Listener()***Function***Declaration**

10 rvcm\_Error rvcm\_AddListener (  
    rv\_Session session,  
    rv\_Name name,  
    rv\_Name subject )

15 **Purpose**

Pre-register an anticipated listener.

**Remarks**

20 Some sending applications can anticipate requests for certified delivery--even before the listening applications begin running. In such situations, the sender can pre-register listeners, so the system begins storing outbound messages in the sender's ledger; when the listener requests certified delivery, it receives the backlogged messages.

25 If the correspondent with this name already receives certified delivery of this subject from this sender session, then rvcm\_AddListener() has no effect.

If the correspondent with this name is disallowed, then rvcm\_AddListener() returns an error. The user can call rvcm\_AllowListener() to supersede the effect of a prior call to  
30 rvcm\_DisallowListener(); then call rvcm\_AddListener() again.

**Parameters**

| Parameter | Description                                                         |
|-----------|---------------------------------------------------------------------|
| session   | A delivery-tracking session.                                        |
| subject   | Anticipate a listener for this subject.                             |
| name      | Anticipate a listener from a correspondent with this reusable name. |

*rvcm\_AddListener()*

### Errors

5

| RVCM_ERR Code                | Indicates                                                                                                                              |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_OK                      | No error. The call completed successfully.                                                                                             |
| RVCM_ERR_INVALID_SESSION     | The function received a session argument that is not a valid rv_session (for example, NULL, or a session that has already terminated). |
| RVCM_ERR_BAD_SESSION_NAME    | The function received an ill-formed reusable name.                                                                                     |
| RVCM_ERR_BAD_ARG             | The function received an illegal argument.<br><br><i>rvcm_AddListener()</i> received a NULL listener name.                             |
| RVCM_ERR_SESSION_NOT_ENABLED | The function received a session that is not enabled for delivery tracking.                                                             |

|                              |                                                                                                                                                                                                 |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_ERR_BAD_SUBJECT         | The function received an ill-formed subject name.<br><br>Either it is NULL, or contained too many total characters, too many characters in an element, too many elements, or an illegal prefix. |
| RVCM_ERR_DISALLOWED_LISTENER | rvcm_AddListener() cannot add this listener because it is disallowed. First call rvcm_AllowListener().                                                                                          |

**Coding Example**

```
cm_err = rvcm_AddListener(sess, "LISTENER_17", subject);
if(cm_err != RVCM_OK)
```

```
5 {
 fprintf(stderr, "Can't add CM listener:\n %s\n",
 rvcm_ErrorText(sess, cm_err));
 exit(-1);
 }
```

10

**See Also**

rvcm\_RemoveListener(), below.

15 **rvcm\_RemoveListener()**

**Function****Declaration**

```
20 rvcm_Error rvcm_RemoveListener (
 rv_Session session,
 rv_Name name, /* listening correspondent name */
 rv_Name subject)
```



**Purpose**

Unregister a specific listener at a specific correspondent, and free associated storage in the sender's ledger.

**5 Remarks**

This function cancels certified delivery of the specific subject to the correspondent with this name. The listening correspondent may subsequently re-register for certified delivery of the subject. (In contrast, `rvcm_DisallowListener()` cancels certified delivery of *all* subjects to the correspondent, *and* prohibits re-registration.)

10

Senders usually call this function when the ledger item for a listening correspondent has grown very large. Such growth indicates that the listener is not confirming delivery, and may have terminated. Removing the listener reduces the ledger size by deleting messages stored for the listener.

15

When a sending program calls this function, certified delivery software in the sender behaves as if the listener had closed the endpoint for the subject. The sending program deletes from its ledger all information about delivery of the subject to the correspondent with this name. The sending program receives a REGISTRATION.

20

CLOSED advisory, to trigger any operations in the callback function for the advisory.

If the listening correspondent is available (running and reachable), it receives a REGISTRATION.NOT\_CERTIFIED advisory, informing it that the sender no longer certifies delivery of the subject.

25

If the correspondent with this name does not receive certified delivery of the subject from this sender session, then `rvcm_RemoveListener()` returns `RVCM_ERR_BAD_SUBJECT`.

**Parameters**

| Parameter | Description                                                                   |
|-----------|-------------------------------------------------------------------------------|
| session   | A delivery-tracking session.                                                  |
| subject   | Cancel certified delivery of this subject.                                    |
| name      | Cancel certified delivery of the subject to the correspondent with this name. |

**5 Errors**

| RVCM_ERR Code            | Indicates                                                                                                                                                                                      |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_OK                  | No error. The call completed successfully.                                                                                                                                                     |
| RVCM_ERR_INVALID_SESSION | The function received a session argument that is not a valid rv_Session (for example, NULL Or a session that has already terminated).                                                          |
| RVCM_ERR_BAD_ARG         | The function received an illegal argument.<br><br>rvcm_RemoveListener() received a NULL listener name or NULL subject; or the sender does not certify delivery of the subject to the listener. |

|                              |                                                                                                                                                                                                                                                                                                                                                       |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_ERR_SESSION_NOT_ENABLED | The function received a session that is not enabled for delivery tracking.                                                                                                                                                                                                                                                                            |
| RVCM_ERR_BAD_SUBJECT         | <p>The function received an ill-formed subject name.</p> <p>Either it is NULL, or contained too many total characters, too many characters in an element, too many elements, or an illegal prefix.</p> <p>rvcm_RemoveListener() received a subject containing wildcard characters; or the sender has not sent certified messages on this subject.</p> |
| RVCM_ERR_DISALLOWED_LISTENER | rvcm_RemoveListener() cannot cancel certified delivery to this listener because the listener is disallowed.                                                                                                                                                                                                                                           |

**Coding Example**

```

cm_err = rvcm_RemoveListener(sess, listener, subject);
5 if(cm_err != RVCM_OK)
 {
 fprintf(stderr, "Can't remove CM listener:\n %s\n",
 rvcm_ErrorText(sess, cm_err));
 exit(-1);
10 }

```

**See Also**

rvcm\_AddListener(), above; and

rvcm\_DisallowListener(), below.

rvcm\_DisallowListener()

## 5 *Function*

### **Declaration**

rvcm\_Error rvcm\_DisallowListener (  
     rv\_Session    session,  
 10      rv\_Name     name )

### **Purpose**

Cancel certified delivery to all listeners at a specific correspondent. Deny subsequent  
 15 certified delivery registration requests from those listeners.

### **Remarks**

Disallowed listeners still receive subsequent messages from this sender, but delivery  
 is not certified. That is:

20

- The listener receives a REGISTRATION.NOT\_CERTIFIED advisory, informing it that the sender has cancelled certified delivery of all subjects.
- If the sender's ledger contains messages sent to the disallowed listener (for  
 25 which this listener has not confirmed delivery), then the system removes those ledger items, and does not attempt to redeliver those messages.
- The system presents subsequent messages (from the cancelling sender) to the listener with sequence number zero, to indicate that delivery is not certified.

30 Senders can promptly revoke the acceptance of certified delivery by calling rvcm\_DisallowListener() within the callback function that processes the REGISTRATION.REQUEST advisory.

This function disallows a correspondent by name. If the correspondent terminates, and another process instance (with the same reusable name) takes its place, the new process is still disallowed by this sender.

- 5 To supersede the effect of `rvcm_DisallowListener()`, call `rvcm_AllowListener()`.

#### Parameters

| Parameter | Description                                                           |
|-----------|-----------------------------------------------------------------------|
| session   | A delivery-tracking session                                           |
| name      | Cancel certified delivery to listeners at the session with this name. |

10

#### Errors

| RVCM_ERR Code             | Indicates                                                                                                                                                       |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_OK                   | No error. The call completed successfully.                                                                                                                      |
| RVCM_ERR_INVALID_SESSION  | The function received a session argument that is not a valid <code>rv_Session</code> (for example, <code>NULL</code> or a session that has already terminated). |
| RVCM_ERR_BAD_SESSION_NAME | The function received an ill-formed reusable name.                                                                                                              |

|                              |                                                                                                          |
|------------------------------|----------------------------------------------------------------------------------------------------------|
| RVCM_ERR_BAD_ARG             | The function received an illegal argument.<br><br>rvcm_DisallowListener() received a NULL listener name. |
| RVCM_ERR_SESSION_NOT_ENABLED | The function received a session that is not enabled for delivery tracking.                               |

**Coding Example**

```

cm_err = rvcm_DisallowListener(sess, "LISTENER_17");
5 if(cm_err != RVCM_OK)
 {
 fprintf(stderr, "Can't disallow CM listener: %s\n",
 rvcm_ErrorText(sess, cm_err));
 exit(-1);
10 }

```

**rvcm\_AllowListener()***Function*

15

**Declaration**

```

rvcm_Error rvcm_AllowListener (
 rv_Session session,
20 rv_Name name)

```

**Purpose**

Invite the named receiver to reinstate certified delivery for its listeners, superseding the effect of any previous calls to rvcm\_DisallowListener().

25

**Remarks**

Upon receiving the invitation to reinstate certified delivery, the system at the listening program automatically sends new registration requests. The sending program accepts these requests, restoring certified delivery.

5

**Parameters**

| Parameter | Description                                                                        |
|-----------|------------------------------------------------------------------------------------|
| session   | A delivery-tracking session.                                                       |
| name      | Accept requests for certified delivery to listeners at the session with this name. |

**Errors**

| RVCM_ERR Code             | Indicates                                                                                                                              |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_OK                   | No error. The call completed successfully.                                                                                             |
| RVCM_ERR_INVALID_SESSION  | The function received a session argument that is not a valid rv_Session (for example, NULL, or a session that has already terminated). |
| RVCM_ERR_BAD_SESSION_NAME | The function received an ill-formed reusable name.                                                                                     |
| RVCM_ERR_BAD_ARG          | The function received an illegal argument. rvcm-AllowListener() received a NULL listener name.                                         |

|                              |                                                                            |
|------------------------------|----------------------------------------------------------------------------|
| RVCM_ERR_SESSION_NOT_ENABLED | The function received a session that is not enabled for delivery tracking. |
|------------------------------|----------------------------------------------------------------------------|

**Coding Example**

```

cm_err = rvcm_AllowListener(sess, "LISTENER_17");
if(cm_err != RVCM_OK)
5 {
 fprintf(stderr, "Can't allow CM listener:In %sin",
 rvcm_ErrorText(sess, cm_err));
 exit(-1);
 }
10 rvcm_NoAutoConfirm()

```

**Function****15 Declaration**

```

rvcm_NoAutoConfirm(
 rv_Session session,
 rvcm_ListenId listenid);

```

**20 Purpose**

Override automatic confirmation of delivery for this listening endpoint.

**Remarks**

25 The default behavior of certified listeners is to automatically confirm message delivery upon return from the data callback function (see `rvcm_Callback`, above). This call selectively overrides this behavior for this specific listening endpoint. (This call does not affect other listening endpoints.)

30 By overriding automatic confirmation, the listener assumes responsibility for explicitly confirming each inbound certified message by calling `rvcm_Confirm()`.



Consider overriding automatic confirmation when processing inbound messages involves asynchronous activity, such as computations in other threads, database queries, or additional network communications.

5

No method exists to restore the default behavior, reversing the effect of this function.

Parameters

Parameter

10

| Parameter | Description                                                                                |
|-----------|--------------------------------------------------------------------------------------------|
| session   | A delivery-tracking session.                                                               |
| listenId  | Override automatic confirmation for inbound certified messages to this listening endpoint. |

Errors

| RVCM_ERR Code                 | Indicates                                                                                                                                                     |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_OK                       | No error. The call completed successfully.                                                                                                                    |
| RVCM_ERR_INVALID_SESSION      | The function received a session argument that is not a valid rv_Session (for example, NULL, or a session that has already terminated).                        |
| RVCM_ERR_NONEXISTENT_LISTENID | rvcm_NoAutoConfirm() received an unusable listenId pointer-either NULL, or it points to something other than an rvcm_ListenId, or it has already been closed. |

**See Also**

`rvcm_Callback` above, and  
`rvcm_Confirm()`, below.

**5 rvcm\_Confirm()**

*Function*

**Declaration**

`rvcm_Confirm()`

10

```

 rv_Session session,
 rvcm_ListenId listenerId,
 rv_Name senderName,
 rvcm_Seq sequenceNumber)

```

15

**Purpose**

Confirm delivery of a certified message.

**Remarks**

20 Use this function only in programs that override automatic confirmation.

The triplet of subject name, sender and sequence number uniquely identifies each certified message. The subject name is already stored in the listening endpoint. The other two components--sender and sequence number--are explicit parameters of this

25

**Parameters**

| Parameter | Description                                               |
|-----------|-----------------------------------------------------------|
| session   | A delivery-tracking session.                              |
| listenId  | Confirm delivery of a message by this listening endpoint. |

|                |                                                                             |
|----------------|-----------------------------------------------------------------------------|
| senderName     | Confirm delivery of a message from the sender with this correspondent name. |
| sequenceNumber | Confirm delivery of the message with this sequence number.                  |

**Errors**

| RVCM_ERR Code                | Indicates                                                                                                                                                                |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_OK                      | No error. The call completed successfully.                                                                                                                               |
| RVCM_ERR_INVALID_SESSION     | The function received a session argument that is not a valid rv_Session (for example, NULL, or a session that has already terminated).                                   |
| RVCM_ERR_BAD_ARG             | The function received an illegal argument.<br><br>rvcm_Confirm( ) received a sequence number argument that is out of range.                                              |
| RVCM_ERR_ID_CONFIRM_CONFLICT | rvcm_Confirm() received a listenId that automatically confirms delivery. rvcm_Confirm() is only valid after overriding automatic confirmation with rvcm_NoAutoConfirm(). |

|                                |                                                                                                                                                         |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_ERR_NONEXISTENT_ID        | rvcm_Confirm() received an unusable listenId pointer-either NULL, or it points to something other than an rvcm_ListenId, or it has already been closed. |
| RVCM_ERR_NONEXISTENT_PUBLISHER | rvcm_confirm() received a senderName argument that is not recognized as the name of a certified sender.                                                 |

**See Also**

rvcm\_Callback; and rvcm\_NoAutoConfirm(), above.

## 5 **rvcm\_ReviewLedger()**

**Function****Declaration**

rvcm\_Error rvcm\_ReviewLedger

10       rv\_Session               session,  
          rv\_Name                subject,  
          rvcm\_ReviewCallback   reviewCallbackFn  
          rv\_Opaque               closureArg );

## 15 **Purpose**

Summarize the delivery status of messages in the ledger,

**Remarks**

20       The callback function receives one message for each matching subject stored in the ledger. For example, when rvcm\_ReviewLedger() receives FOO. \* as its subject argument, it calls the callback function separately for these matching subjects--once for FOO.BAR, once for FOO.BAZ, and once for FOO.BOX.

However, if the callback function returns non-NULL, then `rvcm_ReviewLedger()` returns immediately.

If the ledger does not contain any matching items, `rvcm_ReviewLedger()` returns normally without calling the callback function.

For information about the content and format of the callback messages, see `rvcm_ReviewCallback`, below.

## 10 Parameters

| Parameter                     | Description                                                                                                                                                                                                                                                                                                        |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>session</code>          | A delivery-tracking session.                                                                                                                                                                                                                                                                                       |
| <code>subject</code>          | Review ledger items with this subject.<br><br>If this subject contains wildcard characters ("*" or ">"), then review all items with matching subject names. The callback function receives a separate message for each matching subject in the ledger.                                                             |
| <code>reviewCallbackFn</code> | This function receives the review messages.                                                                                                                                                                                                                                                                        |
| <code>closureArg</code>       | Pass this closure argument to the callback function. This argument must be a pointer, but it can point to any type of data. It contains any information needed by the callback function. the system treats this argument as an opaque closure, forwarding it to the callback function without accessing its value. |

## Errors

| <b>RVCM_ERR Code</b>                | <b>Indicates</b>                                                                                                                       |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>RVCM_OK</b>                      | No error. The call completed successfully.                                                                                             |
| <b>RVCM_ERR_INVALID_SESSION</b>     | The function received a session argument that is not a valid rv_Session (for example, NULL, or a session that has already terminated). |
| <b>RVCM_ERR_BAD_ARG</b>             | The function received an illegal argument. rvcm_ReviewLedger() received a NULL subject name or a NULL review callback function.        |
| <b>RVCM_ERR_NO_MEMORY</b>           | The function could not complete because the operating system denied its request to allocate storage.                                   |
| <b>RVCM_ERR_SESSION_NOT_ENABLED</b> | The function received a session that is not enabled for delivery tracking.                                                             |

**Coding Example**

```
fprintf(stdout, "\nLedger review for subject '%s'. %d:\n",
 subject, reviewMax);
```

5

```
/** See rvcm_ReviewCallback example function, below. */
cm_err = rvcm_ReviewLedger (session, rv_Name)subject,
 myReviewLedgerCallback,
 (rv_Opaque)&reviewMax);
```

```
10 if (cm_err != RVCM_OK)
 {
 fprintf(stderr, "Review ledger failed for '%s':\n\t%s\n",
 subject, rvcm_ErrorText(sess, cm_err));
 }
```

**See Also...**

**rvcm\_ReviewCallback**, above.

## **5 rvcm\_ReviewCallback**

*Datatype*

### **Declaration**

**void\* rvcm\_ReviewCallback (**

10        **rv\_Session**        **session,**  
          **rv\_Name**         **subject,**  
          **rvmsg\_Msg**        **msg,**  
          **rv\_Opaque**        **closureArg )**

### **15 Purpose**

**rvcm\_ReviewCallback** is the function type of callback functions for reviewing the ledger. Applications define functions of this type to process the summary messages from **rvcm\_ReviewLedger()**.

### **20 Remarks**

**rvcm\_ReviewLedger()** calls this callback once for each matching subject in the ledger.

To continue reviewing the ledger, return NULL from this callback function. To stop reviewing the ledger, return non-NULL from this callback function;  
 25 **rvcm\_ReviewLedger()** returns immediately.

30

**Parameters**

| Parameter  | Description                                                                                                                                                                                                                                                                                                                                                                           |
|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| session    | This parameter receives the current session.                                                                                                                                                                                                                                                                                                                                          |
| subject    | This parameter receives the subject name that the message summarizes.                                                                                                                                                                                                                                                                                                                 |
| msg        | This parameter receives a summary message describing the delivery status of messages in the ledger. The table below describes the fields of the summary message.                                                                                                                                                                                                                      |
| closureArg | This parameter receives a closure argument, which the application supplied when it called <code>rvcn_ReviewLedger()</code> . This argument is a pointer, but it can point to any type of data. It contains any information needed by the callback function. The system treats this argument as an opaque closure, forwarding it to the callback function without accessing its value. |

**Message Content**

| Field Name      | Description                                                                                                                          |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------|
| subject         | The subject that this message summarizes.<br>This field has datatype <code>RVMSG_STRING</code> .                                     |
| seqno_last_sent | The sequence number of the most recent message sent with this subject name.<br><br>This field has datatype <code>RVMSG_UTNT</code> . |



|                                |                                                                                                                                                                                                                                                             |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>total_msgs</b>              | The total number of messages with this subject name. This field has datatype RVMSG_UINT.                                                                                                                                                                    |
| <b>total_size</b>              | <p>The total storage (in bytes) occupied by all messages with this subject name.</p> <p>If the ledger contains ten messages with this subject name, then this field sums the storage space over all of them.</p> <p>This field has datatype RVMSG_UINT.</p> |
| <b>listener</b>                | <p>Each summary message can contain one or more fields named listener. Each listener field contains a nested submessage with details about a single registered listener.</p> <p>This field has datatype RVMSG_RVMSG.</p>                                    |
| <b>listener.name</b>           | <p>Within each listener submessage, the name field contains the name of the delivery-tracking listener.</p> <p>This field has datatype RVMSG_STRING.</p>                                                                                                    |
| <b>listener.last_confirmed</b> | <p>Within each listener submessage, the last_confirmed field contains the sequence number of the last message for which this listener confirmed delivery.</p> <p>This field has datatype RVMSG_UINT.</p>                                                    |

**Coding Example**

/\*\* See rvcn\_ReviewLedger() example call, above. \*/

5 void \*

WO 99/09490

PCT/US98/17115

```

myReviewLedgerCallback(rv_Session sess,
 rv_Name subject,
 rvmsg_Msg msg,
 rv_Opaque arg)
5 {
 int * count = (int*) arg;
 /* Print the ledger item. */
 printf("\nLedger item for '%s':\n", subject);
 rvmsg_Print(sess, msg, NULL);
10 printf("\n");

 if (*count)
 {
 (*count)--;
15 if ((*count) > 0);
 {
 /* When count reaches zero, stop. Return from rvcm_ReviewLedger() */
 return((void*)sess);
 }
20 }

 return(NULL); /* Otherwise, continue to the next item. */

```

**See Also**25 *rvcm\_ReviewCallback**rvcm\_ReviewLedger()*, above.*rvcm\_SyncLedgerFile()*

30

*Function***Declaration***rvcm\_Error* *rvcm\_SyncLedgerFile* (*rv\_Session* session);

**Purpose**

Synchronize the ledger file to its storage medium.

**5 Remarks**

When this function returns, the session's current state is safely stored in the ledger file.

10 Delivery-tracking sessions that use synchronous ledger files need not call this function, since the current state is automatically written to the file system before returning.

**Parameters**

| Parameter | Description                                                                 |
|-----------|-----------------------------------------------------------------------------|
| session   | Synchronize the ledger file associated with this delivery-tracking session. |

15

**Errors**

| RVCM Error Code              | Indicates                                                                                                                              |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_OK                      | No error. The call completed successfully.                                                                                             |
| RVCM_ERR_INVALID_SESSION     | The function received a session argument that is not a valid rv_Session (for example, NULL, or a session that has already terminated). |
| RVCM_ERR_SESSION_NOT_ENABLED | The function received a session that is not enabled for delivery tracking.                                                             |

|                               |                                                                                              |
|-------------------------------|----------------------------------------------------------------------------------------------|
| <b>RVCM_ERR_FILE_IO_ERROR</b> | <code>rvcm_SyncLedgerFile()</code><br>encountered an error while writing<br>the ledger file. |
|-------------------------------|----------------------------------------------------------------------------------------------|

**See Also**

`rvcm_Enable()`, above.

5 **rvcm\_Error***Datatype*

10 `rvcm_Error` is an enumerated type for error codes. Table A2 lists the possible `rvcm_Error` values. The user can use the function `rvcm_ErrorText()` to convert `rvcm_Error` message codes to descriptive text. For more information, see `rvcm_ErrorText()` on page 244.

Table A2: Enumerated Values of `rvcm_Error`

15

| <b>RVCM Error Code</b>           | <b>Indicates</b>                                                                                                                                    |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>RVCM_OK</b>                   | No error. The call completed successfully.                                                                                                          |
| <b>RVCM_ERR_INIT_FAILURE</b>     | <code>rvcm_EnableQueue()</code> could not initialize either the certified delivery or fault tolerance components upon which it depends.             |
| <b>RVCM_ERR_INVALID_SESSION</b>  | The function received a session argument that is not a valid <code>rv_Session</code> (for example, NULL, or a session that has already terminated). |
| <b>RVCM_ERR_BAD_SESSION_NAME</b> | The function received an ill-formed reusable name.                                                                                                  |

| RVCM Error Code | Indicates                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                 | <p>rvcm_ListenSubject() received either a NULL callback function, or a NULL listenid pointer.</p> <p>rvcm_ListenInbox() received either a NULL inbox name pointer, a NULL callback function, or a NULL listenid pointer.</p> <p>rvcm_DisallowListener() received a NULL listener name.</p> <p>rvcm_AllowListener() received a NULL Listener name.</p> <p>rvcm_AdclListener() received a NULL listener name.</p> <p>rvcm_RemoveListener() received a NULL listener name or NULL subject; or the sender does not certify delivery of the subject to the listener.</p> <p>rvcm_Send() or rvcm_SendWithReply() received either a NULL subject, or a NULL sequence number pointer.</p> <p>rvcm_ReviewLedger() received a NULL subject name or a NULL review callback function.</p> |

| RVCM Error Code              | Indicates                                                                                                                                                                                                                                                                                                                                                                                                                        |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                              | rvcm_Confirm() received a sequence number argument that is out of range.                                                                                                                                                                                                                                                                                                                                                         |
| RVCM_ERR_NO_MEMORY           | The function could not complete because the operating system denied its request to allocate storage.                                                                                                                                                                                                                                                                                                                             |
| RVCM_ERR_BAD_SUBJECT         | <p>rvcm_Send(),<br/>rvcm_SendWithReply() or<br/>rvcm_ListenSubject() received an ill-formed subject name.</p> <p>Either it is NULL, or contained too many total characters, too many characters in an element, too many elements, a wildcard character, or an illegal prefix.</p> <p>rvcm_RemoveListener() received a subject containing wildcard characters; or the sender has not sent certified messages on this subject.</p> |
| RVCM_ERR_ID_CONFIRM_CONFLICT | <p>rvcm_Confirm() received a listenid that automatically confirms delivery. rvcm_confirm() is only valid after overriding automatic confirmation with rvcm_NoAutoConfirm().</p>                                                                                                                                                                                                                                                  |
| RVCM_ERR_NONEXISTENT_ID      | <p>rvcm_Close(),<br/>rvcm_NoAutoConfirm(), or<br/>rvcm_Confirm() received an unusable listenid pointer--either NULL, or it points to something</p>                                                                                                                                                                                                                                                                               |

| RVCM Error Code                               | Indicates                                                                                                                                                                                                                                                               |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                               | other than an <code>rvcm_ListenId</code> , or it has already been closed.                                                                                                                                                                                               |
| <code>RVCM_ERR_DUPLICATE_SUBJECT</code>       | <code>rvcm_ListenSubject()</code> can open at most one listening endpoint per subject; it cannot open a second listening endpoint for this subject.                                                                                                                     |
| <code>RVCM_ERR_NONEXISTENT_PUBLISHER</code>   | <code>rvcm_Confirm()</code> received a <code>senderName</code> argument that is not recognized as the name of a certified sender.                                                                                                                                       |
| <code>RVCM_ERR_DISALLOWED_LISTENER</code>     | <p><code>rvcm_AddListener()</code> cannot add this listener because it is disallowed. First call <code>rvcm_AllowListener()</code>.</p> <p><code>rvcm_RemoveListener()</code> cannot cancel certified delivery to this listener because the listener is disallowed.</p> |
| <code>RVCM_ERR_SESSION_ALREADY_ENABLED</code> | <code>rvcm_Enable()</code> received a session that is already enabled for delivery tracking. It is illegal to enable a session more than once.                                                                                                                          |
| <code>RVCM_ERR_SESSION_NOT_ENABLED</code>     | The function received a session that is not enabled for delivery tracking.                                                                                                                                                                                              |
| <code>RVCM_ERR_LEDGER_NAME_CONFLICT</code>    | <code>rvcm_Enable()</code> received NULL as the name parameter, but a non-NULL value as the <code>ledgerFile</code> parameter.                                                                                                                                          |
| <code>RVCM_ERR_PARAMETER_CONFLICT</code>      | <p>The function received conflicting values for parameters.</p> <p><code>rvcm_Enable()</code> received <code>RV_FALSE</code> as its <code>requireOldMsgs</code> parameter, and</p>                                                                                      |

| <b>RVCM_Error Code</b>         | <b>Indicates</b>                                                                                                                                                                                              |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                | NULL as its name parameter. A non-reusable name implies a transient correspondent, which cannot have backlog messages.                                                                                        |
| RVCM_ERR_FILE_IO_ERROR         | rvcm_Enable() encountered an error while opening the ledger file. For example, an explicitly named directory does not exist.<br><br>rvcm_SyncLedgerFile() encountered an error while writing the ledger file. |
| RVCM_ERR_FILE_NO_PERMISSION    | File access privileges are insufficient for rvcm_Enable ( ) to open the ledger file.                                                                                                                          |
| RVCM_ERR_FILE_NOT_LEDGER_OWNER | The reusable name recorded in the file differs from the name of this session. ryere_Enable ( ) stopped reading the file.                                                                                      |
| RVCM_ERR_CORRUPT_LEDGER_FILE   | The ledger file is corrupt.<br><br>rvcm_Enable() could read only part of the ledger file into process-based memory. Some information may be lost.                                                             |

**See Also**

rvcm\_ErrorText(), below.



**APPENDIX B: Distributed Queues (Programming Details for C Programmers)**

This Appendix A provides programming details for C programmers wishing to implement Certified message Delivery. The Appendix provides, in Table A1, an overview listing of Certified's messaging Deliver Datatypes and Functions. Each Datatype or Function is then described in greater detail with Cross-references to related Datatypes or Functions.

As described above, Applications can use distributed queues for certified delivery to one of  $n$  listeners (queue member sessions). These distributed queue functions are typically used in combination with certified message delivery.

**Distributed Queue CAPI**

The following Table BA summarizes the datatypes and functions in the distributed queue C API.

Table B1: Distributed Queues: Datatype and Functions

| Item                                        | Description                                      | Page |
|---------------------------------------------|--------------------------------------------------|------|
| <code>rvcm_EnableQueue()</code>             | Enable a session as a distributed queue member   | 248  |
| <code>rvcm_rvcm_SetQueueAcceptTime()</code> | Set the queue time limit for task acceptance.    | 251  |
| <code>rvcm_QueueAcceptTime()</code>         | Return the queue time limit for task acceptance. | 253  |
| <code>rvcm_SetQueueCompleteTime()</code>    | Set the queue time limit for task completion.    | 255  |
| <code>rvcm_QueueCompleteTime()</code>       | Return the queue time limit for task completion. | 257  |

| Item                          | Description                                                                                        | Page |
|-------------------------------|----------------------------------------------------------------------------------------------------|------|
| rvcm_SetQueueListenerWeight() | Set the listener weight of a queue member.                                                         | 261  |
| rvcm_QueueListenerWeight()    | Return the listener weight of a queue member.                                                      | 261  |
| rvcm_SetQueueListenerTasks()  | Set the listener task capacity of a queue member.                                                  | 263  |
| rvcm_QueueListenerTasks()     | Return the listener task capacity of a queue member.                                               | 266  |
| rvcm_Error                    | Datatype. Enumerates error codes for the certified message delivery API and distributed queue API. | 239  |
| rvcm_ErrorTest()              | Return a text string describing an error code                                                      | 244  |

**rvcm\_EnableQueue()***Function***5 Declaration**

```

rvcm_Error rvcm_EnableQueue (
 rv_Session session
 rv_Name name,
 unsigned long schedulerWeight,
 unsigned long schedulerHeartbeat,
 unsigned long schedulerActivation);

```

10

**Purpose**

Enable a session for certified message delivery as part of distributed queue for one-of-

15

**Remarks**

Each member of a distributed queue listens for the same subjects--yet even when n members listen, for each inbound message (or task), exactly one member processes the message.

- 5 Programs must call `rvcm_EnableQueue()` before any other calls related to distributed queues or certified listening.

Once a session becomes a queue member, it cannot resign membership except with `rv_Term()`.

10

### Queue Member Roles

Each distributed queue member session has two distinct roles--as a listener, and as a potential scheduler.

- 15 In the **listener role**, queue member sessions support a limited subset of certified delivery calls: `rvcm_ListenSubject()`, `rvcm_NoAutoConfirm()` and `rvcm_Confirm()`. Queue member sessions do not support any other certified delivery calls (in particular, calls associated with sending certified messages). However, they do support all standard system calls (for example, `rv_Send()`).

20

System fault tolerance software maintains exactly one active scheduler in each queue: if the scheduler process terminates, another member assumes the role of scheduler. The queue member session in the **scheduler role** assigns inbound tasks to listeners in the queue. (A scheduler can assign tasks to its own listener component, but only does so when all other listeners are busy.)

25

### Parameters

| Parameter | Description                                                                                                               |
|-----------|---------------------------------------------------------------------------------------------------------------------------|
| session   | <p>The call enables this session.</p> <p>Before this call, the session must not yet be enabled for delivery tracking.</p> |

| Parameter           | Description                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| name                | The session becomes part of the distributed queue with this reusable name.                                                                                                                                                                                                                                                                                                                         |
| schedulerWeight     | <p>Weight represents the ability of this session to fulfill the role of scheduler, relative to other members of the same queue. The queue members use relative scheduler weight values to elect one member as the scheduler; members with higher scheduler weight take precedence.</p> <p>Acceptable values range from 1 to 65535 (even though the parameter is declared as an unsigned long).</p> |
| schedulerHeartbeat  | <p>The scheduler session sends heartbeat messages at this interval (in milliseconds).</p> <p>All sessions in the queue must specify the same value for this parameter. Acceptable values are the unsigned 32-bit integers (except zero).</p>                                                                                                                                                       |
| schedulerActivation | <p>When the heartbeat signal from the scheduler has been silent for this interval (in milliseconds), the queue member with the greatest scheduler weight takes its place as the new scheduler.</p> <p>All sessions in the queue must specify the same value for this parameter. Acceptable values are unsigned 32-bit integers (except zero).</p>                                                  |

**Errors**

| <b>RVCM_ERR Code</b>                    | <b>Indicates</b>                                                                                                                       |
|-----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>RVCM_OK</b>                          | No error. The call completed successfully.                                                                                             |
| <b>RVCM_ERR_INVALID_SESSION</b>         | The function received a session argument that is not a valid rv_session (for example, NULL, or a session that has already terminated). |
| <b>RVCM_ERR_SESSION_ALREADY_ENABLED</b> | rvcm_Enable() received a session that is already enabled for delivery tracking. It is illegal to enable a session more than once.      |
| <b>RVCM_ERR_NO_MEMORY</b>               | The function could not complete because the operating system denied its request to allocate storage.                                   |
| <b>RVCM_ERR_INIT_FAILURE</b>            | rvcm_EnableQueue() could not initialize either the certified delivery or fault tolerance components upon which it depends.             |

**See Also**

rvcm\_Enable(), Appendix A

5 rvcm\_ListenSubject(), Appendix A

\*\*\*\*\*

**rvcm\_SetQueueAcceptTime()**

Function

10 **Declaration**

#define DEFAULT\_ACCEPT\_TIME (0)

rvcm\_Error rvcm\_SetQueueAcceptTime (

rv\_Session session,

15 unsigned long acceptTime );

**Purpose**

Change the accept time parameter of a queue member session.

**5 Remarks**

When this session, acting as the scheduler, assigns a task to a listener (another queue member session), it sets a timer with this length (in milliseconds). If the timer elapses before the scheduler receives acceptance from the listener, the scheduler reassigns the task to another listener.

10

Zero is a special value, which specifies no limit on the acceptance time---that is, the scheduler does not set a timer, and does not reassign tasks.

Enabling a session as a queue member tacitly sets its accept time parameter to

15 **DEFAULT\_ACCEPT\_TIME** (zero).**Parameters**

| Parameter  | Description                                                                                                                                                           |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| session    | A session in a distributed queue.                                                                                                                                     |
| acceptTime | This value (in milliseconds) becomes the new time limit for acceptance of tasks. It must be less than the complete time parameter (unless the complete time is zero). |

**20 Errors**

|               |                                            |
|---------------|--------------------------------------------|
| RVCM_ERR Code | Indicates                                  |
| RVCM_OK       | No error. The call completed successfully. |

| <b>RVCM_ERR Code</b>             | <b>Indicates</b>                                                                                                                       |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_ERR_INVALID_SESSION         | The function received a session argument that is not a valid rv_session (for example, NULL, or a session that has already terminated). |
| RVCM_ERR_BAD_ARG                 | The function received an illegal argument.                                                                                             |
| RVCM_ERR_SESSION_NOT_ENAB<br>LED | The function received a session that is not enabled for delivery tracking.                                                             |

**See Also**

vcm\_QueueAcceptTime(). below

5

**rvcm\_QueueAcceptTime()**

*Function*

10 **Declaration**

```
#define DEFAULT_ACCEPT_TIME (0)
```

```
rvcm_Error rvcm_QueueAcceptTime (
```

```
15 rv_Session session,
 unsigned long* acceptTime);
```

**Purpose**

Extract the accept time parameter of a queue member session.

20

**Remarks**

When this session, acting as the scheduler, assigns a task to a listener (another queue member session), it sets a timer for the accept time (in milliseconds). If the timer

WO 99/09490

PCT/US98/17115

elapses before the scheduler receives acceptance from the listener, the scheduler reassigns the task to another listener.

Zero is a special value, which specifies no limit on the acceptance time (the scheduler does not set a timer).

Enabling a session as a queue member tacitly sets its accept time parameter to DEFAULT\_ACCEPT\_TIME (zero).

#### 10 Parameters

| Parameter  | Description                                                                             |
|------------|-----------------------------------------------------------------------------------------|
| session    | A session in a distributed queue.                                                       |
| acceptTime | This location receives the stored time limit (in milliseconds) for acceptance of tasks. |

#### Errors

| RVCM_ERR Code | Indicates                                  |
|---------------|--------------------------------------------|
| RVCM_OK       | No error. The call completed successfully. |

15

rvcm\_Qz,QueueAcceptTime()

| RVCM_ERR Code            | Indicates                                                                                                                              |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_ERR_INVALID_SESSION | The function received a session argument that is not a valid rv_session (for example, NULL, or a session that has already terminated). |
| RVCM_ERR_BAD_ARG         | The function received an illegal argument.                                                                                             |



|                              |                                                                            |
|------------------------------|----------------------------------------------------------------------------|
| RVCM_ERR_SESSION_NOT_ENABLED | The function received a session that is not enabled for delivery tracking. |
|------------------------------|----------------------------------------------------------------------------|

**See Also**

rvcm\_SetQueueAcceptTime(), above

5

**rvcm\_SetQueueCompleteTime()**

*Function*

**Declaration**

10 #define DEFAULT\_COMPLETE\_TIME (0)

rvcm\_Error rvcm\_SetQueueCompleteTime (

15 rv\_Session session,  
unsigned long completeTime );

**Purpose**

Change the complete time parameter of a queue member session.

**Remarks**

20 When this session, acting as the scheduler, assigns a task to a listener (another queue member session), it sets a timer with this length (in milliseconds). If the timer elapses before the scheduler receives a completion message from the listener, the scheduler reassigns the task to another listener.

25 Zero is a special value, which specifies no limit on the completion time (the scheduler does not set a timer).

Enabling a session as a queue member tacitly sets its complete time parameter to DEFAULT\_COMPLETE\_TIME (zero).

30

**Parameters**

| Parameter    | Description                                                                                                                                                            |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| session      | A session in a distributed queue.                                                                                                                                      |
| completeTime | This value (in milliseconds) becomes the new time limit for completion of tasks. It must be greater than the accept time parameter (unless the complete time is zero). |

**5 Errors**

| RVCM_ERR Code | Indicates                                  |
|---------------|--------------------------------------------|
| RVCM_OK       | No error. The call completed successfully. |

| RVCM_ERR Code                | Indicates                                                                                                                              |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_ERR_INVALID_SESSION     | The function received a session argument that is not a valid rv_session (for example, NULL, or a session that has already terminated). |
| RVCM_ERR_BAD_ARG             | The function received an illegal argument.                                                                                             |
| RVCM_ERR_SESSION_NOT_ENABLED | The function received a session that is not enabled for delivery tracking.                                                             |

**See Also**

rvcm\_QueueCompleteTime(). below

## 5 **rvcm\_QueueCompleteTime()**

Function

**Declaration**

```
#define DEFAULT_COMPLETE_TIME (0)
```

10

```
rvcm_Error rvcm_QueueCompleteTime (
```

```
 rv_Session session,
 unsigned long* completeTime);
```

15

**Purpose**

Extract the complete time parameter of a queue member session.

**Remarks**

20 When this session, acting as the scheduler, assigns a task to a listener (another queue member session), it sets a timer for the complete time (in milliseconds). If the timer elapses before the scheduler receives a completion message from the listener, the scheduler reassigns the task to another listener.

25 Zero is a special value, which specifies no limit on the completion time (the scheduler does not set a timer).

Enabling a session as a queue member tacitly sets its complete time parameter to DEFAULT\_COMPLETE\_TIME (zero).

30

**Parameters**

| Parameter    | Description                                                                             |
|--------------|-----------------------------------------------------------------------------------------|
| session      | A session in a distributed queue.                                                       |
| completeTime | This location receives the stored time limit (in milliseconds) for completion of tasks. |

**5 Errors**

| RVCM_ERR Code | Indicates                                  |
|---------------|--------------------------------------------|
| RVCM_OK       | No error. The call completed successfully. |

| RVCM_ERR Code                | Indicates                                                                                                                              |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_ERR_INVALID_SESSION     | The function received a session argument that is not a valid rv_session (for example, NULL, or a session that has already terminated). |
| RVCM_ERR_BAD_ABG             | The function received an illegal argument.                                                                                             |
| RVCM_ERR_SESSION_NOT_ENABLED | The function received a session that is not enabled for delivery tracking.                                                             |

**10 See Also**

rvcm\_SetQueueCompleteTime (), below

**rvcm\_Error rvcm\_QueueCompleteTime ()**

Function

## 5 Declaration

#define DEFAULT\_COMPLETE\_TIME (0)

rvcm\_Error rvcm\_QueueCompleteTime (

10 rv\_Session session,  
unsigned long\* completeTime );

## Purpose

Extract the complete time parameter of a queue member session.

15

## Remarks

When this session, acting as the scheduler, assigns a task to a listener (another queue member session), it sets a timer for the complete time (in milliseconds). If the timer  
20 elapses before the scheduler receives a completion message from the listener, the scheduler reassigns the task to another listener.

Zero is a special value, which specifies no limit on the completion time (the scheduler does not set a timer).

25

Enabling a session as a queue member tacitly sets its complete time parameter to DEFAULT\_COMPLETE\_TIME (zero).

## Parameters

30

| Parameter | Description                       |
|-----------|-----------------------------------|
| session   | A session in a distributed queue. |

|              |                                                                                      |
|--------------|--------------------------------------------------------------------------------------|
| completeTime | This location receives the stored time limit (in milliseconds) for completion tasks. |
|--------------|--------------------------------------------------------------------------------------|

**Errors**

| RVCM_ERR Code                | Indicates                                                                                                                                            |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| RVCM-ERR-INVALID-SESSION     | The function received a <i>session</i> argument that is not a valid <i>rv_Session</i> (for example, NULL, or a session that has already terminated). |
| RVCM-ERR-BAD-ARG             | The function received an illegal argument.                                                                                                           |
| RVCM_ERR_SESSION_NOT_ENABLED | The function received a session that is not enabled for delivery tracking.                                                                           |
| RVCM_OK                      | No error. The call completed successfully.                                                                                                           |

- 5    **See Also**  
      *rvcm\_SetQueueCompeteTime ()*, above.

**rvcm\_SetQueueListenerWeight()***Function*

10

**Declaration**

#define DEFAULT\_LISTENER\_WEIGHT (1)

- 15    *rvcm\_Error* *rvcm\_SetQueueListenerWeight* (  
                  *rv\_Session*                    *session*,

unsigned long listenerWeight );

### **Purpose**

Change the listener weight parameter of a queue member session.

5

### **Remarks**

When the scheduler receives a task, it assigns the task to the available listener with the greatest listener weight.

10

A listener is considered available unless either of these conditions are true:

- The pending tasks assigned to the listener exceed its task capacity.
- 15 ■ The listener session is the scheduler. (The scheduler assigns tasks to its own listener only when no other listeners are available.)

Enabling a session as a queue member tacitly sets its listener weight parameter to  
20 DEFAULT\_LISTENER\_WEIGHT (1).

**Parameters**

| Parameter      | Description                                                |
|----------------|------------------------------------------------------------|
| session        | A session in a distributed queue.                          |
| listenerWeight | This value becomes the new listener weight of the session. |

**Errors**

5

| RVCM_ERR Code                | Indicates                                                                                                                                            |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_OK                      | No error. The call completed successfully.                                                                                                           |
| RVCM_ERR_INVALID_SESSION     | The function received a <i>session</i> argument that is not a valid <i>rv_Session</i> (for example, NULL, or a session that has already terminated). |
| RVCM_ERR_BAD_ARG             | The function received an illegal argument.                                                                                                           |
| RVCM_ERR_SESSION_NOT_ENABLED | The function received a session that is not enabled for delivery tracking.                                                                           |

**See Also**

*rvcm\_QueueListenerWeight* (), below.

10

***rvcm\_QueueListenerWeight***()

Function



**Declaration**

```
#define DEFAULT_LISTENER_WEIGHT (1)
```

```
5 rvcn_Error rvcn_QueueListenerWeight (
 rv_Session session,
 unsigned long* listenerWeight);
```

**Purpose**

10

Extract the listener weight parameter of a queue member session.

**Remarks**

15 When the scheduler receives a task, it assigns the task to the available listener with the greatest listener weight.

A listener is considered available unless either of these conditions are true:

- 20 ■ The pending tasks assigned to the listener exceed its task capacity.
- The listener session is the scheduler. (The scheduler assigns tasks to its own listener only when no other listeners are available.)

25

Enabling a session as a queue member tacitly sets its listener weight parameter to DEFAULT\_LISTENER\_WEIGHT (1).

**Parameters**

30

| Parameter | Description                       |
|-----------|-----------------------------------|
| session   | A session in a distributed queue. |

|                |                                                                    |
|----------------|--------------------------------------------------------------------|
| listenerWeight | This location receives the current listener weight of the session. |
|----------------|--------------------------------------------------------------------|

**Errors**

| RVCM_ERR Code                | Indicates                                                                                                                                                  |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_OK                      | No error. The call completed successfully.                                                                                                                 |
| RVCM_ERR_INVALID_SESSION     | The function received a <i>session</i> argument that is not a valid <code>rv_Session</code> (for example, NULL, or a session that has already terminated). |
| RVCM_ERR_BAD_ARG             | The function received an illegal argument.                                                                                                                 |
| RVCM_ERR_SESSION_NOT_ENABLED | The function received a session that is not enabled for delivery tracking.                                                                                 |

5 **See Also**

`rvcm_SetQueueListenerWeight()`, above.

**rvcm\_SetQueueListenerTasks()**

10

*Function*

**Declaration**

15

```
#define DEFAULT_LISTENER_TASKS (1)
```

```

rvcm_Error rvcm_SetQueueListenerTasks (
 rv_Session session,
 unsigned long listenerTasks);

```

5

**Purpose**

Change the listener tasks parameter of a queue member session.

**Remarks**

10

Task capacity is the maximum number of tasks that a listener can accept. When the number of accepted tasks reaches this maximum, the listener cannot accept additional tasks until it completes one or more of them.

15 When the scheduler receives a task, it assigns the task to the listener (a queue member) with the greatest listener weight--unless the pending tasks assigned to that listener exceed its task capacity. When the preferred listener has too many tasks, the scheduler assigns the new inbound task to the listener with the next greatest listener weight.

20

Enabling a session as a queue member tacitly sets its listener tasks parameter to DEFAULT\_LISTENER\_TASKS (1).

Programmers can tune task capacity based on two factors:

25

- Multi-tasking program on multiprocessing hardware.

On a multiprocessing computer, a multi-threaded program that devotes  $n$  threads and  $n$  processors to inbound tasks has task capacity  $n$ .

30

- Communication time lag.

In most distributed queue applications, the communication time is an insignificant fraction of the task turnaround time. That is, the time required to

assign a task and signal its completion is very small compared to the time required to process the task itself. For example, when average task turnaround time is 2000 milliseconds, of which communication time contributes only 10 milliseconds to the total, then task capacity is the same as the number of processors or threads.

However, in some situations communication time can be significant--for example, when the queue members are distributed at distant sites connected by a Wide Area Network (WAN). When communication time is significant, the meaning of task capacity changes; instead of signifying the number of tasks that a listener can process concurrently, it signifies the number of tasks that can fill the listener's capacity despite the communication time lag. For example, when the average task turnaround time is 1500 milliseconds, of which the average task processing time contributes 1000 milliseconds to the total, then setting the task capacity to 3 minimizes the listener's idle time between tasks.

When tuning task capacity to compensate for communication time lag, balance is critical. Underloading a listener (by setting its tasks capacity too low) can cause the listener to remain idle while it waits for the schedule to assign its next task. Conversely, overloading a listener (by setting its task capacity too high) can cause some assigned tasks to wait, while other listeners that might have accepted those tasks remain idle.

## Parameters

| Parameter     | Description                                                                                       |
|---------------|---------------------------------------------------------------------------------------------------|
| session       | A session in a distributed queue.                                                                 |
| listenerTasks | This value becomes the new listener task capacity of the session. The value must be 1 or greater. |

**Errors**

| <b>RVCM_ERR Code</b>         | <b>Indicates</b>                                                                                                                       |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| RVCM_OK                      | No error. The call completed successfully.                                                                                             |
| RVCM_ERR_INVALID_SESSION     | The function received a session argument that is not a valid rv_Session (for example, NULL, or a session that has already terminated). |
| RVCM_ERR_BAD_ARG             | The function received an illegal argument.                                                                                             |
| RVCM_ERR_SESSION_NOT_ENABLED | The function received a session that is not enabled for delivery tracking.                                                             |

5 **See Also**

rvcm\_QueueListenerTasks (), below.

10

**rvcm\_QueueListenerTasks()**

*Function*

15 **Declaration**

```
#define DEFAULT_LISTENER_WEIGHT (1)
```

```
rvcm_Error rvcm_QueueListenerTasks (
```

```

rv_Session session,
unsigned long* listenerTasks);

```

### Purpose

5

Extract the listener tasks parameter of a queue member session.

### Remarks

- 10 Task capacity is the maximum number of tasks that a listener can accept. When the number of accepted tasks reaches this maximum, the listener cannot accept additional tasks until it completes one or more of them.

- 15 When the scheduler receives a task, it assigns the task to the listener (a queue member) with the greatest listener weight--unless the pending tasks assigned to that listener exceed its task capacity. When the preferred listener has too many tasks, the scheduler assigns the new inbound task to the listener with the next greatest listener weight.

- 20 Enabling a session as a queue member tacitly sets its listener tasks parameter to DEFAULT\_LISTENER\_TASKS (1).

### Parameters

| Parameter     | Description                                                               |
|---------------|---------------------------------------------------------------------------|
| session       | A session in a distributed queue.                                         |
| listenerTasks | This location receives the current listener task capacity of the session. |

25

### Errors

| <b>RVCN_ERR Code</b> | <b>Indicates</b>                           |
|----------------------|--------------------------------------------|
| <b>RVCN_OK</b>       | No error. The call completed successfully. |

| <b>RVCN_ERR Code</b>                | <b>Indicates</b>                                                                                                                       |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>RVCN_ERR_INVALID_SESSION</b>     | The function received a session argument that is not a valid rv_session (for example, NULL, or a session that has already terminated). |
| <b>RVCN_ERR_BAD_ARG</b>             | The function received an illegal argument.                                                                                             |
| <b>RVCN_ERR_SESSION_NOT_ENABLED</b> | The function received a session that is not enabled for delivery tracking.                                                             |

**See Also**

rvcm\_SetQueueListenerTasks(), above.

5

1/2





FIG. 1

SUBSTITUTE SHEET (RULE 26)



2/2

*FIG. 2*